

# Product data sheet

Specifications



## Wall mounted enclosure, Spacial S3X, stainless steel 304L, plain door, 300x250x150mm, IP66

NSYS3X302515

### Main

|                      |                                  |
|----------------------|----------------------------------|
| Range                | Spacial                          |
| Product name         | Spacial S3X                      |
| Enclosure type       | Multi-purpose                    |
| Category             | Compact enclosure                |
| Nominal height       | 300 mm                           |
| Nominal width        | 250 mm                           |
| Nominal depth        | 150 mm                           |
| Product installation | Wall-mounting                    |
| Device composition   | 1 body<br>1 lock: door<br>1 door |

### Complementary

|                             |  |
|-----------------------------|--|
| Body type                   | Single piece body, cross-shaped structure<br>Gutter shaped front rail        |
| Door type                   | Plain  |
| Number of doors             | Front face: 1 door(s)  |
| Door opening side           | Reversible (120 °)   |
| Lock type                   | 3 mm double-bar lock   |
| Mounting plate description  | Without mounting plate   |
| Type of gland plate         | Without gland plate  |
| Accessibility for operation | Front  |
| Removable parts             | Door by hinges   |
| Material                    | Body and door: stainless steel 304L<br>Lock: zamak<br>Hinge: stainless steel |
| Surface finish              | Body and door: Scotch-Brite® brushed<br>Lock: chromium plated                |
| Product weight              | 3.53 kg  |

### Environment

|                        |               |
|------------------------|---------------|
| Standards              | IEC 62208     |
| Product certifications | UL 508 type A |

|                                     |                               |
|-------------------------------------|-------------------------------|
| <b>IP degree of protection</b>      | IP66 conforming to IEC 60529  |
| <b>IK degree of protection</b>      | IK10 conforming to IEC 62262  |
| <b>Environmental characteristic</b> | Specific hygiene<br>Corrosive |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type of Package 1</b>       | PCE      |
| <b>Number of Units in Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 32 cm    |
| <b>Package 1 Width</b>              | 26.01 cm |
| <b>Package 1 Length</b>             | 16.51 cm |
| <b>Package 1 Weight</b>             | 3.53 kg  |

## Offer Sustainability

|                                   |   |
|-----------------------------------|---|
| <b>Sustainable offer status</b>   | Green Premium product   |
| <b>REACH Regulation</b>           | <a href="#">REACH Declaration</a>   |
| <b>EU RoHS Directive</b>          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| <b>Mercury free</b>               | Yes   |
| <b>China RoHS Regulation</b>      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| <b>RoHS exemption information</b> | Yes   |
| <b>Environmental Disclosure</b>   | <a href="#">Product Environmental Profile</a>   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

## Recommended replacement(s)