

NOTES: UNLESS OTHERWISE SPECIFIED


RECEPTACLE MATERIAL:
SHELL: ZINC ALLOY, NICKEL PLATED
INSERT AND RETAINING RING: THERMOPLASTIC
SEAL: SILICONE RUBBER


2. BACKSHELL MATERIAL:

SHELL: ALUMINIUM ALLOY, NICKEL PLATED; LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL; BUSHING: EPDM.

3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:
 - 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
- 4.2. WITH ONLY LARGE BUSHING IN PLACE.
- 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC RECEPTACLE DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
- 6.3 MATING PART(S).
- 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.





	AHDM04-2	DM04-24-47SR-059 HD34-24-47SE-059		r]	
	PART NUMBER					DE	SCRIPTION			ITEM	1
QUANTITY		MA	TE	ERI	٩LS	S LI	ST				7
1) All dimensions a		SIGNATUR	ES	DATE	Amphenol			1			
2) Tolerances are a 1 PL DEC ±0.30		DRAWN: J. HEAD		16MAR2020	Amphenor				<i>_</i> 1		
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:			Sine Systems - www.amphenol-sine.com		om				
3) Note reference = X		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036						
APPROVAL: MATERIAL SPECIFICATIONS:		APPROVAL:					Clinton Township, IVII	48036			4
		CUSTOMER:			DUR		E AHDM RECEPT	,	,	THD,	
		THIS DRAWING IS SUPPL INFORMATION ONLY, DES				KIT W	V/ CABLE CLAMF	BACKS	HELL		
PROCESS SPECIFICATIONS: SPECIF		SHOWN HEREON ARE THE THE AMPHENOL CORPOR	TIONS AND PERFORMANCE DAT REON ARE THE PROPERTY OF MOL CORPORATION, NO RIGHT DUCTION ARE IMPLIED, ALL		B	C-	AHDM04-24	-47SR-(A1	
		MANUFACTURING VARIA			SCALE: N	ONE		SHEET	1 of	1	

DWG NO: AHDM04-24-47SR-059

REV: A1 SH: 1

SH. 1

ATM Series™ - Contact Size 20 Options

Machined Contacts, Sockets & Pins					
Part Number Description			AWG	Туре	
AT60-010-2031	Male Contact - Pin, Gold-plated	20	16-18	Machined	
AT62-005-20141	Female Contact - Socket, Gold-plated	20	16-18	Machined	
AT60-010-20141	Male Contact - Pin, Nickel-plated	20	16-18	Machined	
AT62-005-2031	Female Contact - Socket, Nickel-plated	20	16-18	Machined	
AT60-202-2031	Male Contact - Pin, Gold-plated	20	20-22	Machined	
AT62-201-2031	Female Contact - Socket, Gold-plated	20	20-22	Machined	
AT60-202-20141	Male Contact - Pin, Nickel-plated	20	20-22	Machined	
AT62-201-20141	Female Contact - Socket, Nickel-plated	20	20-22	Machined	

Tooling - Machined Contacts					
Part	Part Number	Description			
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)			
5	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)			

	Contact Removal Tools				
Part	Part Number	Description			
	ATRT-100	Used for removal of contacts for A Series™ products			
	AT11-240-2005	Contact Removal Tool, Plastic, Size 20			
	AT13-204-2005	Sealing Plug, Size 20, White			

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-20-0144	Male Contact - Pin, Gold-plated	20	16-22	Stamped & Formed		
AT62-20-0144	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT60-20-0244	Male Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT62-20-0244	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed		
AT60-20-0122	Male Contact - Pin, Nickel-plated	20	16-22	Stamped & Formed		
AT62-20-0122	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT60-20-0222	Male Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT62-20-0222	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed		
AT60-20-0277	Male Contact - Socket, Tin-plated	20	16-22	Stamped & Formed		
AT62-20-0277	Female Contact - Socket, Tin-plated	20	16-22	Stamped & Formed		
AT60-20-0422	Male Contact - Socket, Nickel-plated	20	20-22	Stamped & Formed		
AT62-20-0444	Female Contact - Socket, Gold-plated	20	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts					
Part	Part Number Description				
	MFX-3974	Crimp Die - Size 20 (S&F contacts only)			
	MFX-3976 Crimp Die - Size 20 (\$&F contacts only) 20-22AWG -04XX Series				
	MFX-3978	Crimp Die - Size 20 (S&F contacts only) 20-22AWG -02XX Series			
K	АТТ-20-00	Hand Crimp Tool - Size 20, 20AWG (S&F contacts only)			

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins					
Part Number Description		Size	AWG	Туре	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined	
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined	
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined	
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined	
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined	
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined	

Tooling - Machined Contacts				
Part	Part Number	Description		
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)		
5	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)		

	Contact Removal Tools					
Part	Part Number	Description				
	ATRT-100	Used for removal of contacts for A Series™ products				
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16				
4	A114017	Sealing Plug, Size 16, White				

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Type		
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed		
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed		
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed		
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed		
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed		
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed		
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed		
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed		
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed		
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed		
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed		
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed		
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed		
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed		
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed		
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed		

	Tooling - Stamped & Formed Contacts					
Part	Part Number Description					
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)				
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)				
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)				
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)				
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)				
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)				
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)				

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021