

## VGA Audio + Video over IP Extender Receiver over Cat5/Cat6, RS-232 Serial and IR Control, 1920 x 1440, 328 ft. (100 m), TAA

MODEL NUMBER: B160-100-VSI



Receives IP-based audio + video signal transmitted point-to-point from a source 328 ft. away via Cat5e/6 cable or through a dedicated Ethernet network switch

### Features

#### VGA Audio + Video, Serial and IR Control Signals over Cat5/6 Cabling

- Receives IP-based audio + video transmitted point-to-point from a source 328 ft. away
- Add low-cost network switches between transmitter and receiver to continue extending distance up to 328 ft. per switch

#### Create a Multi-In, Multi-Out Installation Using B160-Series Transmitters and Receivers

- Connect up to 64 transmitters and 255 receivers through multiple dedicated managed network switches
- IGMP-enabled switches allow centralized control over which sources show on which displays
- Displays video from any analog or digital source, so you can mix and match technologies and use existing sources and monitors

#### Enhanced Technical Features

- Supports video resolutions up to 1920 x 1440, including 1080p
- Uses H.264 video compression standard
- Transmits on 20–60 kHz IR frequency
- Extends IR control signals that control a source from a remote display
- Supports RS-232 serial baud rates up to 57600 Bps
- HDCP and 3D compatible when used with a DisplayPort or HDMI transmitter

#### Plug-and-Play Functionality

- No software or drivers required
- Hardware included for mounting on wall, rack or pole
- Compatible with all B160-Series A/V over IP transmitters

### Highlights

- Compatible with B160-Series A/V over IP transmitters
- Display video from any source, analog or digital
- Supports video resolutions up to 1920 x 1440, including 1080p
- Scales up to multi-in, multi-out installation with network switch
- Plug and play—no software or drivers required

### Package Includes

- Receiver unit
- External power supply (Input: 100–240V, 50/60 Hz, 0.5A; Output: 5V 2A)
- Plug adapters for U.S., U.K., Europe and Australia
- IR-In cable
- 3.5 mm to DB9 adapter cable (M/M)
- Mounting hardware
- Owner's manual

**TAA-Compliant**

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

| OVERVIEW                                       |                                                                              |
|------------------------------------------------|------------------------------------------------------------------------------|
| UPC Code                                       | 037332196750                                                                 |
| Product Type                                   | Receiver                                                                     |
| Technology                                     | IR; VGA/SVGA; A/V over IP; Cat5/5e; Cat6                                     |
| VIDEO                                          |                                                                              |
| Max Supported Video Resolution                 | 1920 x 1440 @ 60Hz                                                           |
| Max 1280 x 720 (720p) Range (ft)               | 328                                                                          |
| Max 1920 x 1080 (1080p) Range (ft)             | 328                                                                          |
| Max 1920 x 1200 Range (ft)                     | 328                                                                          |
| Receiver/Transceiver Video Output              | VGA                                                                          |
| Receiver - Number of Video Outputs             | 1                                                                            |
| Range Extension using other Tripp Lite product | 328 ft.                                                                      |
| Recommended Cabling                            | N202-Series Cat6 Patch Cable                                                 |
| Other Tripp Lite product used to extend range  | network switch                                                               |
| Max Supported Color Depth                      | 24-bit True Color                                                            |
| HDR Support                                    | No                                                                           |
| 3D Video Supported                             | No                                                                           |
| Maximum Signal Range (ft)                      | 328                                                                          |
| Maximum Signal Range (m)                       | 100                                                                          |
| Maximum Signal Range Details                   | 328 ft via Cat6/275 ft via Cat5e                                             |
| AUDIO                                          |                                                                              |
| Audio Output                                   | 3.5mm                                                                        |
| Audio Specification                            | Stereo Audio                                                                 |
| INPUT                                          |                                                                              |
| AC Power Adapter Plug(s)                       | AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America |
| AC Power Adapter Input Specs (V / Hz / A)      | 100-240V / 50/60Hz / 1.0A                                                    |

|                                              |                                                                                                                                                                |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AC Power Adapter Output Specs (V / A)        | 5V / 2A                                                                                                                                                        |
| AC Power Adapter Cord Length (ft.)           | 4.5                                                                                                                                                            |
| AC Power Adapter Cord Length (m)             | 1.4                                                                                                                                                            |
| Bus Powered                                  | No                                                                                                                                                             |
| <b>POWER</b>                                 |                                                                                                                                                                |
| Power Source Type                            | AC Adapter                                                                                                                                                     |
| AC Plug Type                                 | NEMA 1-15P; BS1363; CEE 7/16 Schuko; AS/NZS 3112                                                                                                               |
| Power Source                                 | Unit (Included)                                                                                                                                                |
| Power Over Cable (PoC) Support               | No                                                                                                                                                             |
| DC Barrel Plug                               | OD: 5.5 x 2.1 x 7.5mm, Positive Pin, Negative Sleeve                                                                                                           |
| Power Consumption (Watts)                    | 5.3                                                                                                                                                            |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                                                                                                |
| LED Indicators                               | RJ45 Output (Green / Power, Orange / Signal), Channel Signal (Red), Power (Green)                                                                              |
| <b>PHYSICAL</b>                              |                                                                                                                                                                |
| Color                                        | Black                                                                                                                                                          |
| Material of Construction                     | Steel                                                                                                                                                          |
| Included Mounting Accessories                | Wallmount                                                                                                                                                      |
| Number of Displays                           | 1                                                                                                                                                              |
| Optional Mounting Accessory Notes            | Can DIN Mount using Tripp Lite Bracket <a href="http://triplite.eaton.com/din-rail-mounting-bracket-for-digital-signage-version-2-B110-DIN-02">B110-DIN-02</a> |
| Form Factor/Mounting Options                 | Box; Wall-mount                                                                                                                                                |
| Rackmountable                                | Yes                                                                                                                                                            |
| Shipping Dimensions (hwd / in.)              | 2.10 x 6.40 x 10.20                                                                                                                                            |
| Shipping Weight (lbs.)                       | 1.80                                                                                                                                                           |
| Unit Dimensions (hwd / in.)                  | 0.000 x 0.000 x 0.000                                                                                                                                          |
| Unit Packaging Type                          | Box                                                                                                                                                            |
| Unit Weight (lbs.)                           | 0.2                                                                                                                                                            |
| Unit Weight (kg)                             | 0.09                                                                                                                                                           |
| Housing                                      | Metal                                                                                                                                                          |
| <b>ENVIRONMENTAL</b>                         |                                                                                                                                                                |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)                                                                                                                                      |
| Storage Temperature Range                    | 5° to 122°F (-15° to 50°C)                                                                                                                                     |
| Relative Humidity                            | 0% to 85%, Non-Condensing                                                                                                                                      |

|                                              |                                                                 |
|----------------------------------------------|-----------------------------------------------------------------|
| BTUs                                         | 18.1 BTU/Hr                                                     |
| <b>COMMUNICATIONS</b>                        |                                                                 |
| Signal Range (ft.)                           | 328                                                             |
| Signal Range (m)                             | 100                                                             |
| EDID Compatible                              | No                                                              |
| IR Remote Extension Support                  | Yes                                                             |
| RS-232 Serial Extension Support              | Yes                                                             |
| Consumer Electronics Control (CEC) Supported | No                                                              |
| Latency                                      | 2-3 seconds                                                     |
| USB Extension Support                        | No                                                              |
| <b>CONNECTIONS</b>                           |                                                                 |
| Number of Ports                              | 5                                                               |
| Side A - Connector 1                         | 3.5MM (FEMALE); HD15 (FEMALE)                                   |
| Side B - Connector 1                         | RJ45 (FEMALE)                                                   |
| Daisy-chainable / Cascadable                 | No                                                              |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                                                                 |
| 10/100 Ethernet Extension Support            | No                                                              |
| Built-In Equalizer                           | No                                                              |
| Driver Required                              | No                                                              |
| Recommended Category Cable                   | N202-Series Cat6 Patch Cable                                    |
| <b>STANDARDS &amp; COMPLIANCE</b>            |                                                                 |
| External Power Supply Certifications         | BSMI; CB; CCC; CE; FCC; GS; PSE; RCM; TUV; UL; cUL              |
| Product Compliance                           | RoHS; CE (Europe); REACH; FCC (USA); Trade Agreements Act (TAA) |
| <b>WARRANTY &amp; SUPPORT</b>                |                                                                 |
| Product Warranty Period (Worldwide)          | 1-year limited warranty                                         |