

Readability **0.2 g - 0.0005 lb / 0.5g - 0.001 lb / 1 g - 0.002 lb**

► Features



- High contrast LCD screen
- Auto shut-off
- Large stainless steel pan
- RS232 interface
- Full range tare function
- Robust ABS housing
- Leveling feet
- Multiple weighing units

► Standard Functions

- Weighing
- Parts counting
- Checkweighing
- Accumulation

► Accessories Included

- Power adaptor
- Rechargeable battery
- Clear protective cover

TECHNICAL DATA

Model	VE-CW6S	VE-CW15S	VE-CW30S
Capacity	6 kg / 12 lb	15kg / 30 lb	30 kg / 60 lb
Readability	0.2 g / 0.0005 lb	0.5g / 0.001 lb	1 g / 0.002 lb
Repeatability	±0.4 g	±1 g	±2 g
Linearity	±0.4 g	±1 g	±2 g
Weighing Units	g, kg, lb		
Calibration	External		
Pan Size	300 x 232 mm / 11.8" x 9.1"		
Stabilization Time	2 seconds		
Interface	RS232		
Display	LCD, digit height 20 mm / 0.787"		
Housing	ABS plastic		
Operating Environment	-10° to 40°C / 14° to 104°F		
Overall Dimensions	360 x 300 x 110mm /14.2" x 12" x 4.3"		
Power Supply	110/240V, 50/60 Hz AC Adapter and rechargeable battery		
Net Weight	3.7 kg/ 8.157 lb		
Warranty	1 year		