

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - TE Connectivity ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	E1	REVISED PER ECR-17-008392	29JUN2017	BW	KR

- ACCEPTS MATE-N-LOK™ SOCKET 350217.
- SOCKETS PROTRUDE 0.20 MAX AT MATING END; RECESSED 3.90 MIN. AT BACK END.
- CAUTION: THIS CONNECTOR IS NOT POLARIZED. IT HAS BEEN DESIGNED IN ACCORDANCE WITH THE INTERNATIONAL ORGANIZATION FOR STANDARDIZATION DESIGN DEPICTED IN DOCUMENT 5599/III DATED 4-27-77 UNDER RESOLUTION 59 OF ISO/TC 131/SC5/WG 3. INTENDED USE IS AS SHOWN IN FIGURE 1-1.
- ▲ VISUAL POLARIZING FEATURE.
- DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED, CONDITION. ADDITIONAL 2% GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

FIGURE 1 - 1

THIS HOUSING TO BE INSTALLED IN VALVE BODY

SOCKET HOUSING CUT OUT

1-640406-0  
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER 11-24-92			NAME	
DIMENSIONS: mm[INCHES]		CHK R. SWING 11-24-92			VALVE CONNECTOR, SOCKET HOUSING, 5 CIRCUIT, UNIVERSAL MATE-N-LOK™	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. SELF 12-11-92	APPLICATION SPEC		SIZE	RESTRICTED TO
0 PLC ± - 1 PLC ± - 2 PLC ± 0.10 3 PLC ± - 4 PLC ± - ANGLES ± - FINISH -		PRODUCT SPEC	SCALE	SHEET	REV	
MATERIAL NYLON UL 94V-2 NATURAL		WEIGHT 0.000000	A2 00779	DRAWING NO C-640406	1 OF 1	
		CUSTOMER DRAWING	4:1		E1	

CUSTOMER DRAWING

1471-9 (1/15)

640406