

Phytion™		Device Programmers and Development Tools for Microcontrollers				
Home	Products	E-Shop	Support	Contact	News	Site Map

Quick Links

- Help Desk
- Downloads
- All Programmers
- Device Search
- Tools Catalogs

Shopping Cart

Items: 0

Total: \$0.00


Your Account

Products

- Development Tools
 - ARM
 - 8051
 - Other
- Device programmers
 - All Models
 - Universal
 - In-System
 - Gang
 - Adapters
- Custom made tools
- OEM tools

AE-TS56-161-4

DIP40/ TSOP56 specialized adapter for FLASH memory.



Description:

DIP40/TSOP56 specialized adapter for FLASH memory. Device package dimensions: 14 x 20 mm, 0.5 mm pitch.

Supported Devices:

Click the device programmer model below to get an appropriate list of the devices supported by this programmer with this adapter:

- [ChipProg-48](#)
- [ChipProg-G4](#)
- [ChipProg-40](#)

[Adapter wiring diagram.](#)

Adapter Connection Table:

DIP -40	TSOP-56	U1, 74AHC573	U2, 74AHC573	C1, 150pF	C2, 0.1uF
1	38				
2					
3		11	11	1	
4	44				
5	27				
6	28				
7	14				
8	56				
9	43				
10	19				
11	20				
12	21				
13	22				
14	23				
15	24				
16	25				
17	29				
18	13				
19					
20	12,31,45,46	1, 10	1, 10	2	2
21	30				
22	32				
23	34	2			
24	35		2		
25	36	3			
26	37		3		
27	39	4			
28	40		4		
29	41	5			
30	42		5		

	31	47	6		
	32	48		6	
	33	49	7		
	34	50		7	
	35	51	8		
	36	52		8	
	37	53	9		
	38	54		9	
	39				
	40	33,15	20	20	1
		10		14	
		11		15	
		16		16	
		17		17	
		18		18	
		55		19	
	1		12		
	2		13		
	3		14		
	4		15		
	5		16		
	6		17		
	7		18		
	8		19		
	9			13	
	26			12	

Copyright © 2007-2010 Phytton, Inc.

Phone: 718-259-3191 • E-mails: info@phyton.com, sales@phyton.com, support@phyton.com