

Specification Sheet

Part Number: 133-02353



Bundling clip with gradual transition provides security to bundles around panel edges.

Flanged ends prevent slip in tape wrap.

4x oval prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.

Angled Bundling Clip, 65mm Long, 0.60 - 6.75mm Panel Thickness, PA66HIRHSUV, Black, 4000/ctn

Article Number	133-02353
Type	FTOVALSTRNRLF
Color	Black (BK)
Quantity Per	carton
Product Description	Designed for use with cable ties or electrical tape, bundling clips provide a simple method of securing wire and cable bundles. HellermannTyton offers these clips in standard and standoff orientations, with a variety of mounting options.
Short Description	Angled Bundling Clip, 65mm Long, 0.60 - 6.75mm Panel Thickness, PA66HIRHSUV, Black, 4000/ctn
Global Part Name	FTOVALSTRNRLF-PA66HIRHSUV-BK

Length L (Imperial)	2.55
Length L (Metric)	64.7
Fixation Method	Fir Tree
Height H (Imperial)	0.89
Height H (Metric)	22.6
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.26" x 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.2 x 12.2 mm 7.0 x 12.0 mm 6.5 x 12.5 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB

Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)