



- NOTES:
- FOR HAND INSERTION USE SPACING 0.130 [3.30]
FOR AUTOMATED INSERTION USE SPACING 0.135 [3.43]
 - DIMENSIONS SHOWN FOR REFERENCE ONLY.
 - HEX NUT AND FLAT WASHER SUPPLIED UNASSEMBLED.
 - MATERIAL:
HOUSING, HEX NUT - COPPER ALLOY, NICKEL PLATED
INSULATOR HOUSING - THERMOPLASTIC
TERMINAL INSULATORS - PHENOLIC
FLAT WASHER - STEEL, NICKEL PLATED
PIN, SPRING, TERMINALS - COPPER ALLOY, SILVER PLATED
 - E** IT IS RECOMMENDED THAT THE JACK MOUNTING NUT BE TIGHTENED
SNUG BY HAND BEFORE APPLYING A FINAL TIGHTENING TORQUE OF
8-10 LB-IN USING HAND TOOLS ONLY. POWER DRIVER OR IMPACT
DRIVERS ARE NOT RECOMMENDED.
 - THESE PRODUCTS ARE RoHS COMPLIANT.

						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					UNLESS OTHERWISE SPECIFIED	SIZE	WIDTH	MULT	LBS/M	TEMPER
					1. ALL DIMENSIONS IN INCHES [mm]	FINISH				MATERIAL
					- TWO PLACE DECIMALS ±0.02 [0.5]	SPEC No.				SPEC No.
					- THREE PLACE DECIMALS ±0.005 [0.13]	FIRST USED ON		SCALE 2:1		Switchcraft®
E	28397	6-11-21	PC	TJK		DATE DRAWN	BY	CHKD	APVD	
D	26591	8-6-10	RS	TJK		3-4-99	MM	MM	JF	
								3-4-99	3-4-99	
REV	ECO NUMBER	DATE	BY	APVD		NAME POWER JACKS				PART No.
REVISIONS					DO NOT SCALE DRAWING	L712RA, L722RA, L732RA, RoHS				L712RA L722RA L732RA
										REV E