Obsolete

•M•C•C•

Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Small surface mounting type
- Low reverse current and low forward voltage
- High reliability
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0

Maximum Ratings

	-		
Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V _{RM}	40	V
DC Reverse Voltage	V _R	25	V
Mean Rectifying Current	Ι _ο	400	mA
Peak Forward Surge Current	I _{FSM}	2	А
Junction Temperature	ΤJ	-40 to 125	°C
Storage Temperature	T _{STG}	-30 to 85	°C
V	- 310		Ű


Bectrical Characteristics @25°CUnless Otherwise Specified

Parameter	Symbol	Min.	Тур.	Max.	Unit
Forward Voltage @ I _F =10mA @ I _F =200mA	V _F			0.3 0.5	V
Reverse Current @V _R =25V	I _R			70	uA
Marking: D30					

Marking: D3Q

0.4 Amp Schottky Barrier Rectifier 25 Volts

RB495D




www.mccsemi.com

RB495D



Micro Commercial Components



www.mccsemi.com



Micro Commercial Components

IMPORTANT NOTICE

Micro Commercial Components Corp . reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes .
Micro Commercial Components Corp . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights , nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp . and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by Micro Commercial Components Corp. are not intended for use in Medical,

Aerospace or Military Applications.

www.mccsemi.com