



CONFIDENTIAL & PROPRIETARY INFORMATION
 This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM (INCH)



NOTES:

- MAGNET PROPERTIES PER N-50M:
 Br: 14,100-14,500 G
 Hc: 12,700-13,300 Oe
 Hci: ≥14,000 Oe
 T max: 100 C
- SUPPLIED MAGNETIZED THROUGH THE THICKNESS
- PARTS ARE NICKEL PLATED FOR 15 HRS SALT SPRAY MIN.



REV	DESCRIPTION	DATE	BY

TOLERANCES
 (UNLESS OTHERWISE NOTED)

DECIMAL METRIC
 X.XX = ± .01 X.X = ± .25
 X.XXX = ± .005 X.XX = ± .13

ANGLES
 ± .5°

DO NOT SCALE DRAWING

Alliance LLC 1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 2 mm x 2 mm DISC MAGNET		
SENSOR MAGNET		P/N: ALC2020M
GRADE: N-50M	Drwg by: BT	REV LEVEL: A
COATING: Nickel	Appr by: DV	Approval: 06-15-2017