

## Han 3EMC-HTE-M25 w. glued seal



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 62 003 1447  |
| Specification      | Han 3EMC-HTE-M25 w. glued seal  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19620031447">https://b2b.harting.com/19620031447</a> |

### Identification

|                             |  |
|-----------------------------|--|
| Category                    | Hoods/Housings                               |
| Series of hoods/housings    | Han <sup>®</sup> EMC                         |
| Type of hood/housing        | Hood   |
| Description of hood/housing | for Han-Brid <sup>®</sup><br>With glued seal |

### Version

|                      |  |
|----------------------|--|
| Size                 | 3 A  |
| Version              | Top entry                                  |
| Cable entry          | 1x M25                                     |
| Locking type         | Single locking lever                       |
| Field of application | Hoods/Housings for higher EMC requirements |
| Pack contents        | Please order seal screw separately.        |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                      |
| Note on the limiting temperature       | For use as a connector according to IEC 61984.       |
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 With seal screw<br>IP67 With seal screw |
| Type rating acc. to UL 50 / UL 50E     | 12   |

### Material properties

|                         |               |
|-------------------------|---------------|
| Material (hood/housing) | Zinc die-cast |
|-------------------------|---------------|



**Pushing Performance**  
Since 1945

## Material properties

|                                     |                            |
|-------------------------------------|----------------------------|
| Surface (hood/housing)              | Uncoated                   |
| Colour (hood/housing)               | Unpainted                  |
| Material (seal)                     | NBR                        |
| RoHS                                | compliant                  |
| ELV status                          | compliant                  |
| China RoHS                          | e                          |
| REACH Annex XVII substances         | Not contained              |
| REACH ANNEX XIV substances          | Not contained              |
| REACH SVHC substances               | Not contained              |
| Fire protection on railway vehicles | EN 45545-2 (2020-08)       |
| Requirement set with Hazard Levels  | R1 (HL 1-3)<br>R7 (HL 1-3) |

## Specifications and approvals

|           |        |
|-----------|--------|
| CE        | Yes    |
| Approvals | DNV GL |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 10                                       |
| Net weight                     | 65.4 g                                   |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140171411                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |