

14x51mm Modular Fuse Holder

RoHS



Catalogue Symbol:

CH14(# of poles)**B**: standard fuse holder
 CH141**BNX**: neutral fuse holder
 CH14(# of poles)**BN**: standard fuse holder and neutral
 CH14(# of poles)**BI**: fuse holder with neon indicator
 CH14(# of poles)**BNI**: fuse holder with neutral and neon indicator
 CH14(# of poles)**BMS-F**: fuse holder with microswitch (pre-breaking/fuse operation/presence)
 CH14(# of poles)**BNMS-F**: fuse holder with neutral and microswitch (pre-breaking/fuse operation/presence)
 CH14(# of poles)**BMS**: fuse holder with microswitch (fuse operation)
 CH143**BNMS**: 3-pole and neutral with microswitch (fuse operation)
 CH14(# of poles)**B-PV**: photovoltaic fuse holder

Compatible Fuse Links:

C14G and C14M 14x51mm fuse links
 PV-(amp rating)A14F Photovoltaic gPV fuse links
 FW ferrule fuse links, see table below

Part Number	Maximum Continuous Fuse Current	Part Number*	Maximum Continuous Fuse Current
FWH-5A14F	5A	FWP-5A14F	5A
FWH-10A14F	10A	FWP-10A14F	10A
FWH-15A14F	14A	FWP-15A14F	14A
FWH-20A14F	18A	FWP-20A14F	18A
FWH-25A14F	21A	FWP-25A14F	21A
FWH-30A14F	22A	FWP-30A14F	22A
FWX-5A14F	5A	FWP-32A14F	27A
FWX-10A14F	10A	FWP-40A14F	32A
FWX-15A14F	15A	FWP-50A14F	38A
FWX-20A14F	20A		
FWX-25A14F	24A		
FWX-30A14F	27A		

*Please contact Cooper Bussmann Application Engineers if you wish to use a FWP fuse link with a striker option.

Standards/Certifications:

- IEC 60269-1, 60269-2, 60947-1, 60947-3
- UL4248-1 Fuse Holders, UL 486A-B Wiring Terminals
- CSA C22.2 No 4248.1 Fuse Holders, C22.2 No 65 Wiring Terminals

-  UL File: E14853

Description: Compact DIN-Rail mount fuse holders for 14x51mm cylindrical fuse links. Available in different versions with fuse indicator, neutral and microswitch. CH14B-PV models for use with solar gPV fuse links available in 1 and 2-pole versions

Packaging: 1-pole: 6 per pack
 2-pole: 3 per pack
 3-pole: 2 per pack
 4-pole: 1 per pack

Technical Data:

Number of Poles: 1 to 4

Rated Voltage	IEC	UL
CH14B Series	690Vac	750Vac
CH14B-PV Series	1500Vdc	N/A

Rated Current	IEC	UL
CH14B Series	50A	50A
CH14B-PV Series	32A	N/A

Rated Power Acceptance: 5W
 Maximum Power Acceptance: 6W
 Utilisation Category: 50A at AC-21B 690V/AC-22B 500V
 Pollution Degree: 3
 Protection Index: IP20
 Rated Insulation Voltage: 8kV U_{imp}
 SCCR Rating: 200kA, 33kAdc for CH14B-PV
 Terminal Size: 1.5-35mm² /16-3 AWG solid cable, Cu only
 1.5-25mm² / 16-4 AWG stranded cable, Cu only
 Service Temperature: -20°C to 70°C
 Storage Temperature: -40°C to 80°C

Environmental

- RoHS compliant

Features

- Silver-plated copper contacts
- Engineered polymer enables greater performance with melting temperature in excess of 300°C
- Ventilation zones optimized for a better heat dissipation
- Accessory to isolate the fuse holder via a padlock
- IP20 security accessory to improve protection
- Label holder for easy circuit identification
- PV version rated at 1500Vdc (IEC only) for use with gPV fuse links

14x51mm Modular Fuse Holder

Part Numbers System

Old Part Number	New Part Number	Number of Poles	Description
Neutral Only			
CH141DNX	CH141BNX	1	Neutral cylindrical fuse holder
Fuse Holder Only			
CH141D	CH141B	1	1-pole cylindrical fuse holder
CH142D	CH142B	2	2-pole cylindrical fuse holder
CH143D	CH143B	3	3-pole cylindrical fuse holder
CH144D	CH144B	4	4-pole cylindrical fuse holder
Fuse Holder and Neutral			
CH141DN	CH141BN	2	1-pole + neutral cylindrical fuse holder
CH143DN	CH143DN	4	3-pole + neutral cylindrical fuse holder
Fuse Holder with Neon Indicator			
CH141DI	CH141BI	1	1-pole cylindrical fuse holder with neon indicator
CH142DI	CH142BI	2	2-pole cylindrical fuse holder with neon indicator
CH143DI	CH143BI	3	3-pole cylindrical fuse holder with neon indicator
CH144DI	CH144BI	4	4-pole cylindrical fuse holder with neon indicator
Fuse Holder with Neon Indicator and Neutral			
CH141DNI	CH141BNI	2	1-pole + neutral cylindrical fuse holder with neon indicator
CH143DNI	CH143BNI	4	3-pole + neutral cylindrical fuse holder with neon indicator
Fuse Holder with Microswitch			
CH141DMS	CH141BMS	1	1-pole cylindrical fuse holder with microswitch (fuse operation)
CH141DMS-F	CH141BMS-F	1	1-pole cylindrical fuse holder with microswitch (pre-breaking/fuse operation/presence)
CH143DMS	CH143BMS	3	3-pole cylindrical fuse holder with microswitch (fuse operation)
CH143DMS-F	CH143BMS-F	3	3-pole cylindrical fuse holder with microswitch (pre-breaking/fuse operation/presence)
Fuse Holder with Microswitch and Neutral			
CH143DNMS-F	CH143BNMS-F	4	3-pole + neutral cylindrical fuse holder with microswitch (pre-breaking/fuse operation/presence)
CH143DNMS	CH143DNMS	4	3-pole + neutral cylindrical fuse holder with microswitch (fuse operation)

Accessories

Part Number	Description	Unit Packing
AL-D	Multi-pole ganging clips, one kit will gang up to 4-poles together	12
CH14-HP	Multi-pole handle pins, one kit will gang up to 12 handles together	12
CH14-L	Lockout padlock support, it will accept up to 5mm diameter padlock shank	5
CH14-IP20	IP20 protection accessory, provides IP20 protection to terminals with 10mm ² or less cable	12
CH14-MS1	1-pole microswitch accessory, provides detection of a blown fuse link	5
CH14-MS3	3-pole microswitch accessory, provides detection of a blown fuse link	3

14x51mm Modular Fuse Holder



Dimensions (mm)

