Double function: clean cutting, precise crimping

- > with two crimping dies for end caps on Bowden cable sheaths and ferrules for wire rope
- > comfortable work due to slim design and internal opening spring
- > bolted joint for precise blade guidance, readjustable
- > high leverage for reduced effort
- > cutting edge hardness (approx. 64 HRC)
- > chrome vanadium heavy-duty steel; forged, manifold oil-hardened



Crimping of the ferrules onto the traction cable



Crimping of the end caps on the Bowden cable sheath



95 61 190









> Cuts all wire ropes

without splaying,

ferrules

including those that are extremely strong > Not for electrical end

95 62 190








95 62 190 T BKA*

Pliers with integrated tether attachment point for tool drop protection system





Internal opening spring

Transport lock and opening limiter



				0	Crimp profiles					
						Cutting capacities				
Product Number	Packaging	4→ Inch mm		Head	Handles	Ø Inch Ø mm	Ø Inch Ø mm	Ø Inch Ø mm	Ø Inch Ø mm	∆ ∆ lbs
95 61 190	X	7 1/2 190	**************************************		plastic coated	9/32 7.0	13/64 5.0	5/32 4.0	3/32 2.5	0.69
95 62 190	X	7 1/2 190	**************************************	burnished	multi-component grips	9/32 7.0	13/64 5.0	5/32 4.0	3/32 2.5	0.69
95 62 190 T BKA	X	7 1/2 190	**************************************	burnished	multi-component grips, integrated tether attachment point	<mark>9/32</mark> 7.0	1 <mark>3/64</mark> 5.0	5/32 4.0	3/32 2.5	0.83