

## T18R6-4K2



**Article Number:** 111-01779

**Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Blue/Yellow Striped, 50/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T18R6-4K2

**Type** T18R

**Color** Blue (BU)  
Yellow (YE)

**Features and Benefits**

- Inside serrations allow for strong hold on cables and wire bundles.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Blue/Yellow Striped, 50/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 18.0 lbs

**Minimum Tensile Strength (Metric)** 80.0 N

**Length L (Imperial)** 4.0 "

**Length L (Metric)** 100.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Variant** Inside Serrated

**Width W (Imperial)** 0.1 "

**Width W (Metric)** 2.45 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 0.86 "

**Bundle Diameter Max. (Metric)** 22.0 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 50

**Carton Quantity** 10000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)  
**Material Shortcut** PA66  
**Flammability** UL94 V2  
**Halogenfree** Yes  
**Operating Temperature** -40°F to +185°F (-40°C to +85°C)  
**ROHS Compliant** Yes  
**Certification/Specification** MIL 53421  
UL-ZODZ2.E64139  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** No