



TECHNICAL:
 LISTED: cULus
 RATED SUPPLY VOLTAGE: 120 VAC
 RATED CURRENT: UP TO 15 AMPS OR CABLE RATING
 RESET TYPE: AUTOMATIC OR MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 4-6 mA
 OVERLOAD CURRENT: 90 AMP 125 VAC
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	LENGTH "A"	POWER-UP
1301530043	15051-1A	2 FT 7 IN	1 FT ± 1 IN	AUTO
1301530052	15051-6A	7 FT 7 IN	6 FT ± 2 IN	AUTO
1301530046	15051-25A	26 FT 7 IN	25 FT ± 2 IN	AUTO
1301530049	15051-50A	51 FT 7 IN	50 FT ± 4 IN	AUTO
1301530044	15051-1M	2 FT 7 IN	1 FT ± 1 IN	MANUAL
1301530053	15051-6M	7 FT 7 IN	6 FT ± 2 IN	MANUAL
1301530047	15051-25M	26 FT 7 IN	25 FT ± 2 IN	MANUAL
1301530050	15051-50M	51 FT 7 IN	50 FT ± 4 IN	MANUAL

FUNCTIONAL SYMBOLS $\nabla_A = 0$ $\nabla_C = 0$ $\nabla_D = 0$ DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: MIGRATION TO ECTR/NX		
	DIMENSION UNITS	SCALE	 120V 15A INLINE GFCI W/ 1447 & 1547 NEMA 5-15 PRODUCT CUSTOMER DRAWING		
	INCH	NTS			
	GENERAL TOLERANCES (UNLESS SPECIFIED)				
ANGULAR TOL ± 0.5°					
4 PLACES ±		EC NO: 684571	2021/11/08		
3 PLACES ±		DRWN: VASUTHKARP	2022/01/20		
2 PLACES ± 0.13		CHK'D: DNGUYEN62	2022/02/02		
1 PLACE ± 0.25		APPR: HKNEELAND	2022/02/02		
0 PLACES ±		INITIAL REVISION:	2013/02/06		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DRWN: HRUIZ01	2015/04/20		
THIRD ANGLE PROJECTION		APPR: JFMURPHY	2015/04/20		
D-DRAWING		SERIES	MATERIAL NUMBER	CUSTOMER	
D-DRAWING		D-DRAWING	SEE TABLE	GENERAL MARKET	
D-DRAWING		D-DRAWING	130153	1 OF 1	