

GENERAL SPECIFICATIONS:


RATING: CABLE TYPE / SIZE: TEMPERATURE RATING: CABLE JACKET COLOR: OVERALL LENGTH (L): CABLE OUTER DIAMETER: END 'A' TERMINATION: END 'B' TERMINATION: APPROVALS PLUG: APPROVALS CONNECTOR: 10A / 250 V AC H05VV-F, 3 X 1.0 mm ² 70° C BLACK 2500 ± 50 mm 7.0 + 0.2 mm IEC 320/C13; YC-12 BRAZILIAN; YP-04 INMETRO, UL BR UL BR

NOTES:

1. CORD AND PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).

PACKING:

HANKED MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.





				DASH NO.	PART NO	REV.			DESCRIPTION	NOTES	
	เล	INMETRO OCP 0004		TABULATION BLOCK							
	BR OCP-0029							NCES: ANGULAR +/- 1*	GlobTek, Inc. www.globtek.com 186 Veterans Dr. North Tel. 201-784-1000 Fa		
are	Contents of this document re subject to change without rior notice	Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applica-	Globtek product are not authorized for use as mission critical components in life support, haz- ardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	INIT.BY:	SO DATE: 12/01/09	.xx +	MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/013		DWG TITLE: BRAZILIAN DETACHABLE CORDSET		
				DRAWN:	NF DATE: 12/01/09	FSCN G, CC		SIZE A		REV. C	
				APRVD: I	HM DATE: 12/01/09	SCA	SCALE: NONE		PART NO: 204B4272M5701(R)	SHEET 1/1	