



Product: [9495](#)

High Perform Instr, 1 Tri #14 Str TC, PVC Ins E1, PVC Jkt, PLTC

Request Sample

### Product Description

High Performance Instrumentation, 1 Triad 14AWG (42x30) Tinned Copper, PVC Insulation E1 Color Code, PVC Outer Jacket, PLTC

### Technical Specifications

#### Product Overview

|                        |   |
|------------------------|---|
| Suitable Applications: | Instrumentation, Sensors, Valves, Positioners, RTD, 4-20mA, 0-10V |
|------------------------|---|

#### Construction Details

##### Conductor

| Element  | No. of Elements | Size   | Stranding | Material           |
|----------|-----------------|--------|-----------|--------------------|
| Triad(s) | 1               | 14 AWG | 42x30     | TC - Tinned Copper |

##### Insulation

| Element  | Material                 | Nom. Thickness     | Nom. Insulation Diameter | Color Code          |
|----------|--------------------------|--------------------|--------------------------|---------------------|
| Triad(s) | PVC - Polyvinyl Chloride | 0.022 in (0.56 mm) | 0.119 in (3.02 mm)       | Black , White , Red |

##### Outer Jacket

| Material                 | Nom. Thickness    | Nom. Diameter      | Ripcord |
|--------------------------|-------------------|--------------------|---------|
| PVC - Polyvinyl Chloride | 0.042 in (1.1 mm) | 0.355 in (9.02 mm) | Yes     |

|                                   |                    |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.355 in (9.02 mm) |
|-----------------------------------|--------------------|

#### Electrical Characteristics

##### Electricals

| Element  | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Max. Current                 |
|----------|--------------------|-------------------------------|------------------------------|
| Triad(s) | 2.8 Ohm/1000ft     | 27 pF/ft (89 pF/m)            | 8 Amps per conductor at 25°C |

##### Voltage

| UL Voltage Rating |
|-------------------|
| 300 V (PLTC, CMG) |

#### Mechanical Characteristics

##### Temperature

| UL Temperature | Operating       |
|----------------|-----------------|
| 105°C          | -30°C to +105°C |

|              |          |
|--------------|----------|
| Table Notes: | AWM 80°C |
|--------------|----------|

##### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 3.6 in (91 mm)  | 3.6 in (91 mm)    |

|                    |                 |
|--------------------|-----------------|
| Max. Pull Tension: | 160 lbs (73 kg) |
| Bulk Cable Weight: | 82 lbs/1000ft   |

## Standards and Compliance

|                                  |   |
|----------------------------------|---|
| Environmental Suitability:       | Indoor/Outdoor, Indoor, Sunlight Resistance, Burial   |
| Flammability / Reaction to Fire: | UL 1685 UL Loading, T-29-520, IEEE 1202, FT4  |
| NEC / UL Compliance:             | Article 725, Article 727, Article 800, CMG, ITC, PLTC   |
| AWM Compliance:                  | AWM 2464  |
| CEC / C(UL) Compliance:          | CMG   |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)   |

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.527 Revision Date: 04-14-2023 |
|----------------------|--|

## Part Numbers

### Variants

| Item #       | Color  | UPC          | Footnote |
|--------------|--------|--------------|----------|
| 9495 0601000 | Chrome | 612825253990 | C        |
| 9495 0602500 | Chrome | 612825254003 | Z        |
| 9495 060500  | Chrome | 612825254010 | C        |

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.