

### NOT RECOMMENDED FOR NEW DESIGNS NO RECOMMENDED REPLACEMENT contact our Technical Support Center at 1-888-INTERSIL or www.intersil.com/tsc



www.intersil.com/products/isl6215

# ISL6215

Precision Multi-Phase Buck PWM Controller for Intel Mobile Voltage Positioning IMVP-III

FN9051 Rev 0.00 November 2001

The ISL6215 Multi-Phase Buck PWM control IC with ISL6205 half bridge gate drivers provide a precision voltage regulation system for advanced microprocessors in notebook computers. Three-phase operation and discrete external gate drivers address the thermal management issues and load demand of Intel's latest high performance processors. This control IC also features both input voltage feed-forward and average current mode control for excellent dynamic response, lossless current sensing using MOSFET's R<sub>DS(ON)</sub> and user selectable switching frequencies from 200kHz to 1MHz.

The ISL6215 includes a 5 bit digital-to-analog converter (DAC) that dynamically adjusts the CORE PWM output voltage from 0.600V to 1.70V and conforms to the Intel IMVP III mobile VID specification. The ISL6215 also has logic inputs to detect between Performance / Battery mode and Deep Sleep / Deeper Sleep suspend modes. Single channel PWM, to improve efficiency at light load operation, is available during Deeper Sleep operation. A precision reference, remote sensing and proprietary architecture with integrated processor mode-compensated droop provide excellent static and dynamic CORE voltage regulation.

Another feature of this controller IC is the PGOOD monitor circuit which is held low until CORE voltage increases, during its Soft-Start sequence, to within 10mV of the programmed voltage. The Overvoltage threshold is 1.725V and CORE output voltage above this level results in converter shutting down. Undervoltage, 86% of programmed level, results in PGOOD being pulled low. Overcurrent protection features pulse by pulse current limiting. PGOOD, Overvoltage, Undervoltage and Overcurrent features provide monitoring and protection for the microprocessor and power system.

The ISL6215 IC package is available in 28 lead SSOP.

# Ordering Information

PART NUMBER	TEMP. ( <sup>o</sup> C)	PACKAGE	PKG. NO.
ISL6215CA	-10 to 85	28 Lead SSOP	M28.15
ISL6215CA-T	-10 to 85	28 Lead SSOP Tape and Reel	M28.15

## Features

- Multi-Phase Power Conversion
- High Efficiency Current Sensing
  - Option for thermal compensation
  - Optional Current-Sense Resistor for Precision Overcurrent
- Precision CORE Voltage Regulation
  - 1% System Accuracy Over Temperature
- Microprocessor Voltage Identification Input
  - 5-Bit VID Input
  - 1.000V to 1.700V in 50mV steps
  - 0.600V to 1.000V in 25mV steps
  - Programmable Droop Voltage
- · ALTEN and ALTV voltage bypass VID code
- · OFFSET input for DEEP SLEEP Mode
- · Programmable slew rate control on output voltage
- Excellent Dynamic Response
  - Combined Voltage Feed-Forward and Average Current Mode Control
- Over Voltage, Undervoltage and Overcurrent Protection
- · 2 or 3 Phase "User Selectable" Operation
- · Power-Good Output
- · User selectable Switching Frequency of 200kHz -1MHz
  - 400kHz 3.0MHz Effective Ripple Frequency

## Pinout

### ISL6215 (28 Lead SSOP)

### TOP VIEW

<b>VID 0</b>		<sup>28</sup> VCC
VID 1 2	-	27 ALTEN
VID 2 🖪	-	26 SOFT
VID 3 🛛		25 PGOOD
VID 4 📑		24 EN
		23 ISEN1
FSET 7	-	<sup>22</sup> PWM1
		21 PWM2
FB 🦻		20 ISEN2
	1	19 ISEN3
OCSET 1	ī	<sup>18</sup> PWM3
ALTV 🗉		17 NODV
OFFSET 1	5	16 VSEN
GND 1	4	15 VRTN

© Copyright Intersil Americas LLC 2001. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

For additional products, see www.intersil.com/en/products.html

Intersil products are manufactured, assembled and tested utilizing ISO9001 quality systems as noted in the quality certifications found at <a href="http://www.intersil.com/en/support/qualandreliability.html">www.intersil.com/en/support/qualandreliability.html</a>

Intersil products are sold by description only. Intersil may modify the circuit design and/or specifications of products at any time without notice, provided that such modification does not, in Intersil's sole judgment, affect the form, fit or function of the product. Accordingly, the reader is cautioned to verify that datasheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com

FN9051 Rev 0.00 November 2001

