Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, plain door, completely sealed, 1500x1000x420mm, IP65, IK10

NSYPLA15104G

| *** |
|-----|
| |

| Range | Thalassa |
|---------------------------|--|
| Product name | Thalassa PLA |
| Enclosure type | Multi-purpose |
| Product or component type | Suitable enclosure |
| Version | PLA |
| Nominal height | 1500 mm |
| Nominal width | 1000 mm |
| Nominal depth | 420 mm |
| Enclosure mounting | Floor-standing |
| Device composition | 1 top part 1 bottom part 2 side part 2 door 2 rear panel |

Complementary

| Body type | Sealed top and bottom part assembled with side parts |
|-----------------------------|--|
| Door type | Plain front |
| Number of doors | 2 door(s) |
| Door opening side | Right and left (120 °) |
| Lock type | 4 points lock, 5 mm double-bar |
| Accessibility for operation | Rear Front |
| Removable parts | Door by hinges Rear panel by fixing element |
| Material | Polyester reinforced with fibreglass |
| Colour | Grey (RAL 7035) |
| Standards | UL 508 A IEC 62208 |
| NEMA degree of protection | NEMA 1 NEMA 2 NEMA 13 NEMA 12 |
| Product certifications | DNV Marine UL/cUL listed |

Veritas

| Electrical insulation class | Class II |
|-------------------------------------|--|
| | |
| Environment | |
| IP degree of protection | IP65 conforming to IEC 60529 (completely sealed) |
| IK degree of protection | IK10 conforming to IEC 62262 (plain door) |
| Fire resistance | 960 °C conforming to IEC 62208 |
| Ambient air temperature for storage | -3590 °C |
| Packing Units | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 44.500 cm |
| Package 1 Width | 102.500 cm |
| Package 1 Length | 150.500 cm |
| Package 1 Weight | 60.600 kg |
| Unit Type of Package 2 | PAM |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 220.000 cm |
| Package 2 Width | 100.000 cm |
| Package 2 Length | 120.000 cm |
| Package 2 Weight | 134.200 kg |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| | EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| RoHS exemption information | Yes |
| | |

Recommended replacement(s)

Environmental Disclosure

Product Environmental Profile