


CK2,5-ED-0,50ST AU

Order No.: 1674804

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1674804>Turned 2.5 crimp contact, individual male contact, core diameter 0.5
mm², gold-plated**Commercial data**

GTIN (EAN)	
sales group	D090
Pack	100 pcs.
Customs tariff	74152900
Catalog page information	Page 528 (PC-2009)

Product notesWEEE/RoHS-compliant since:
02/01/2006

[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data**Electrical characteristics**

Note	For HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers, the quality of a crimp connection is determined by the DIN EN 60 352-2, gold-plated contacts recommended for $U > 5 \text{ V}$ and $I > 5 \text{ mA}$
Ambient temperature (operation)	-40 °C ... 125 °C

Mechanical characteristics

Conductor cross-section	0.5 mm ²
Connection cross-section AWG	20
Stripping length of the individual wire	7.5 mm (9.5 mm at HC-M-HV...)
Insertion/withdrawal cycles	≥ 500

General characteristics

Type	Individual male contact
Connection method	Crimp connection
Connection	for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers. The quality of a crimp connection is determined by the DIN EN 60 352-2. for HC-M-06, HC-M-HV, HC-M-08, HC-M-20, HC-A, HC-BB, HC-B and HC-HV contact carriers, the quality of a crimp connection is determined by the DIN EN 60 352-2 Gold-plated contacts are recommended for U > 5 V and I > 5 mA.

Material data

Contact material	Copper alloy
Contact surface material	Hard gold-plated

Certificates / Approvals




Certification GOST, UL

Accessories

Item	Designation	Description
Tools		
1676734	CK1,6/2,5-MWZ	Assembly tool, for CK 1.6... crimp contacts for small conductor cross sections
1662722	CK2,5-EWZ	Contact removal tool, for turned and rolled CK- 2.5-... contacts
1687419	CRIMPFOX-1,6/2,5-ED-4,0	Crimping pliers, for turned contacts, CK 1.6 ED... and CK 2.5 ED...

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;