

Cable marker - UCT-WMTB (29X8) GY - 0803326

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Cable marker, Sheet, gray, unlabeled, can be labeled with: THERMOMARK CARD, BLUEMARK CLED, BLUEMARK LED, TOPMARK LASER, Mounting type: Assembly with cable binders, Lettering field: 29 x 8 mm



Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 STK |
| Minimum order quantity | 10 STK |
| Weight per Piece (excluding packing) | 10.0 g |
| Custom tariff number | 39269097 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|----------------|----------|
| Length (b) | 9.6 mm |
| Width (a) | 47.6 mm |
| Cable diameter | > 2.9 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
|---------------------------------|-------------------|

General

| | |
|--|-------------------------------------|
| Note | Can be labeled via thermal transfer |
| Color | gray |
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | V0 |
| Material | PC V0 |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 6 |
| Number of individual labels per row | 1 |
| Printability | Thermal transfer |
| | UV LED technologie |

Cable marker - UCT-WMTB (29X8) GY - 0803326

Technical data

General

| | |
|---|-------------------------------------|
| | Direct laser marking |
| Device | 5146464 THERMOMARK CARD |
| | 5147888 BLUEMARK LED |
| | 5147999 BLUEMARK CLED |
| | 0831831 TOPMARK LASER |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result | Test passed |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN 60068-2-11:2000-02 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result | Test passed |
| Marking mounting type | Assembly with cable binders |

Standards and Regulations

| | |
|--|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V0 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 8.0 | 27400401 |
| eCl@ss 9.0 | 27400401 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001530 |
|----------|----------|

Accessories

Accessories

Cable marker - UCT-WMTB (29X8) GY - 0803326

Accessories

Magazine

Magazine - THERMOMARK CARD-UCT-MAG20 - 0830751



Magazine for the THERMOMARK CARD printer, for accommodating UCT sheets (UCT-EM (10x7))