

https://www.phoenixcontact.com/us/products/2404169

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Emalytics Supervisor license for CSV database driver

Commercial data

Item number	2404169
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DR18
Product key	DRHBAA
GTIN	4055626349206
Weight per piece (including packing)	23.4 g
Weight per piece (excluding packing)	23.4 g
Customs tariff number	49119900
Country of origin	US

PHŒN

2404169

https://www.phoenixcontact.com/us/products/2404169

Technical data

Product properties	
Product type	Building management system
Area of application	Building technology
System properties	
Type of software	On-premise
Intended use for the software	Automation
	Engineering
License information	
Type of license	Driver license
License duration	nicht relevant
Functionality	
Integrated function	Analysis
	Data acquisition
	Diagnostics
	Startup
	Communication
	Configuration
	Project planning
	Simulation
Target system	Server
Supported controllers	ILC 2050 BI
Number of data points	not relevant
Number of clients	nicht relevant
System requirements	
Operating system	Windows [®] 10
	Windows [®] 8.1 Enterprise (64-Bit)
	Windows [®] Server 2012 Standard
	Windows [®] Server 2012 R2 Standard
Hard disk memory	min. 4 GByte (more recommended depending on the archiving requirements)
RAM	min. 1 GByte
Interfaces	1 x Ethernet (10/100 Mbps), RJ45
Languages supported	German, English
Screen resolution	1024 x 768 pixel(s) ,or higher

2404169

https://www.phoenixcontact.com/us/products/2404169



Classifications

ECLASS

ECLASS-11.0	27242590
ECLASS-13.0	27242590
ECLASS-12.0	27242590

ETIM

	ETIM 8.0	EC001435	
UNSPSC			
	UNSPSC 21.0	43233600	

2404169

https://www.phoenixcontact.com/us/products/2404169



Accessories

ILC 2050 BI - Controller

2403160 https://www.phoenixcontact.com/us/products/2403160



Modular Inline controller for automation applications in the fields of building technology, infrastructure, and energy technology. Equipped with two logically separated IP address interfaces each with 2 integrated Fast Ethernet ports. Configurable assignment of the Ethernet ports for the use of the spanning-tree protocol, daisy chain and redundant ring structures for maximum availability. Four LAN, two USB, and two RS-485 interfaces are integrated. The data point connections can be extended with up to 63 Inline I/O modules: digital and analog, function terminals for DALI, pulse counting, MBUS or serial interfaces.

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com