



Support terminal, blue, spring-type terminal, for front plate mounting

product brand name	SIRIUS ACT	
product designation	Support terminal	
product type designation	3SU1	
<b>General technical data</b>		
suitability for integration	yes	
degree of pollution	3	
surge voltage resistance rated value	6 kV	
protection class IP		
• of the enclosure	IP40	
• of the terminal	IP20	
reference code according to IEC 81346-2	S	
Substance Prohibittance (Date)	10/01/2014	
<b>Connections/ Terminals</b>		
type of electrical connection	spring-loaded terminals	
• of modules and accessories	Spring-type terminal	
<b>Ambient conditions</b>		
ambient temperature		
• during operation	-25 ... +70 °C	
• during storage	-40 ... +80 °C	
<b>Installation/ mounting/ dimensions</b>		
fastening method of modules and accessories	Front plate mounting	
height	36 mm	
width	9.8 mm	
depth	23.4 mm	
<b>Certificates/ approvals</b>		
General Product Approval	Declaration of Conformity	Test Certificates

[Confirmation](#)



[Type Test Certificates/Test Report](#)

Marine / Shipping

other



[Environmental Confirmations](#)

other

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3SU1400-1DA50-3AA0>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3SU1400-1DA50-3AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-1DA50-3AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3SU1400-1DA50-3AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3SU1400-1DA50-3AA0&lang=en)



last modified:

12/18/2020