



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Slow-acting (T); Rated voltage: 250 V, Rated current: 0.5 A

Business data

Article number	2924.0
Article name	SI 5x20 0,500A-T
GTIN (EAN)	4044211056490
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.86 g
Weight per piece (including packaging)	0.9 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

Technical data

Dimensions

Length	20 mm
Diameter of contact cap	5.2 mm
Dimensions	5x20 mm

Ratings

Rated voltage	250 V
Rated current	0.5 A

Materials

Contact caps	Brass
Surface	Nickel
Tube	Glass

Further technical data

Trigger characteristic	Time-lag (T)
Rated breaking capacity	35 A @ AC 250 V
Voltage drop	120 mV
Power loss (@ 1.5 I _n)	0.2 W
Melting integral I ² t _s	0.9 A ² s

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

2924.0 SI 5x20 0,500A-T



Approvals

Standards and regulations

Standards / specifications

IEC 60127-2/3 EN 60127-2/3 VDE 0820-2/3

Data sheet

2924.0 SI 5x20 0,500A-T



Media

Accessories
