

Aug. 1. 2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| APPLICABLE STANDARD | | IEC 61169-32 | | | |
|--|---|--|----------------------------|---------------------------|----------|
| RATING | OPERATING TEMPERATURE RANGE | -55°C TO +125°C(95%RH MAX) | STORAGE TEMPERATURE RANGE | -55°C TO +85°C(95%RH MAX) | |
| | POWER | _____ W | CHARACTERISTIC IMPEDANCE | 50Ω (0 TO 65 GHz) | |
| | PECULIARITY | _____ | APPLICABLE CABLE | _____ | |
| SPECIFICATIONS | | | | | |
| ITEM | TEST METHOD | | REQUIREMENTS | QT | AT |
| CONSTRUCTION | | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | | X | X |
| ELECTRIC CHARACTERISTICS | | | | | |
| CONTACT RESISTANCE | 100 mA MAX (DC OR 1000 Hz). | CENTER CONTACT | 4 mΩ MAX. | X | X |
| | | OUTER CONTACT | 2 mΩ MAX. | X | X |
| INSULATION RESISTANCE | 500 V DC. | 5000 MΩ MIN. | | X | X |
| VOLTAGE PROOF | 500 V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX. | | NO FLASHOVER OR BREAKDOWN. | X | X |
| VOLTAGE STANDING WAVE RATIO | FREQUENCY 0 TO 65 GHz. TEST METHOD IS BACK TO BACK. | VSWR 1.2 MAX. (0 TO 30GHz) | | X | X |
| | | VSWR 1.4 MAX. (30 TO 60GHz) | | | |
| | | VSWR 1.6 MAX. (60 TO 65GHz) | | | |
| INSERTION LOSS | FREQUENCY TO GHz | dB MAX. | | - | - |
| MECHANICAL CHARACTERISTICS | | | | | |
| CONTACT INSERTION AND EXTRACTION FORCES | EXTRACTION GAUGE: $\phi 0.495 \begin{smallmatrix} 0 \\ -0.005 \end{smallmatrix}$ [mm] STEEL GAUGE. | INSERTION FORCE | N MAX. | - | - |
| | | EXTRACTION FORCE | 0.05 ~ 2 N MIN. | X | X |
| INSERTION AND WITHDRAWAL FORCES | MEASURED BY APPLICABLE CONNECTOR. | INSERTION FORCE | N MAX. | - | - |
| | | EXTRACTION FORCE | N MIN. | - | - |
| MECHANICAL OPERATION | 500 TIMES INSERTIONS AND EXTRACTIONS. | 1) CONTACT RESISTANCE: CENTER CONTACT 6 mΩMAX. OUTER CONTACT 4 mΩMAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | X | - |
| VIBRATION | FREQUENCY 10 TO 2000 Hz SINGLE AMPLITUDE 0.75 mm, 196 m/s ² AT 10 CYCLES FOR 3 DIRECTIONS. | 1) NO ELECTRICAL DISCONTINUITY OF 1 μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | X | - |
| SHOCK | 980 m/s ² DIRECTIONS OF PULSE 6 ms AT 3 TIMES FOR 3 DIRECTIONS. | | | X | - |
| ENVIRONMENTAL CHARACTERISTICS | | | | | |
| DAMP HEAT,CYCLIC | EXPOSED AT -10 TO +65 °C, 90~96 % TOTAL 10 CYCLES (240 h) | 1) INSULATION RESISTANCE: 100 MΩ MIN. (AT HIGH HUMIDITY) 2) INSULATION RESISTANCE: 5000 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | X | - |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55 → -- → +125 → -- °C TIME 30 → 3 → 30 → 3 min. UNDER 5 CYCLES. | NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | | X | - |
| CORROSION SALT MIST | EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h. | VSWR CHARACTERISTIC SHALL BE MET. | | X | - |
| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE | |
| | 1 DIS-D-00005254 | AH. MARUYAMA | NK. NINOMIYA | 20200917 | |
| REMARK | | | APPROVED | MH. OGUSU | 20190108 |
| NOTE MEASUREMENT STATE OF BACK TO BACK | | | CHECKED | MH. OGUSU | 20190108 |
| PORT1 PORT2 | | | DESIGNED | AH. MARUYAMA | 20190108 |
| UNLESS OTHERWISE SPECIFIED, REFER TO IEC 60512. | | | DRAWN | AH. MARUYAMA | 20190108 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | DRAWING NO. | ELC-380932-12-00 | | |
| | SPECIFICATION SHEET | | PART NO. | HV-R-SR2 (12) | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL338-0010-0-12 | 1/1 |