

# Product data sheet

Specifications



## Sealed pressure balance valves IP68 ØM12 F120 liters/hour when 0,07 bar

NSYCAG12LPH2

### Main

Range	ClimaSys
Product	ClimaSys CA
Range compatibility	Thalassa (Thalassa PLS) Thalassa (Thalassa PLM) Thalassa (Thalassa TBS) Thalassa (Thalassa TBP)
Product or component type	Pressure release valve
Accessory / separate part category	Thermal management accessory
Environmental characteristic	Water resistant
Fixing mode	Screwed
Device composition	1 valve
Quantity per set	Set of 10

### Complementary

Material	Membrane: acrylic co-polymer PA6
Diameter	10.2 mm
Height	30 mm
Width	140 mm
Flame retardance	V2
Operating temperature	-40...150 °C
Permeability	120 l/h
Pressure difference	< 0.1 bar

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	14.0 cm
Package 1 Length	12.0 cm
Package 1 Weight	4.0 g

Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	3.0 cm
Package 2 Width	14.0 cm
Package 2 Length	12.0 cm
Package 2 Weight	40.0 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)