



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Albaloy Plating (Copper-Tin-Zinc) Pl. 80 Min. Thick
 3. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick
 4. Teflon
 5. Passivated

Crimped Ferrule
 Hex Crimp Size .429 (10.9)
 Contact Pin to Solder

RoHS Compliant

9	Ferrule	Note 1	Note 2	1
8	Contact Pin	Note 1	Note 3	1
7	Retainer Ring	SUS 304	Note 5	1
6	Gasket	Silicone	Red	1
5	Contact Body	Note 1	Note 2	1
4	Insulator	Note 4	Natural	1
3	Barrel	Note 1	Note 2	1
2	Body	Note 1	Note 2	1
1	Shell	Note 1	Note 2	1
No.	Description	Material	Finish	Q'ty

Dimensions are in Inches
 Unless Otherwise Specified
 Tolerances
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

Part No.	
Approved	Date 12-14-2018
Checked	Date 12-14-2018
Drawn	Date 12-14-2018

NTE Electronics	
Title	N Crimp Plug (For RG-213/U Cable)
Drawing No.	06-N003
File No.	

No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	2.5/1	Issue	A
-----	-------------	----------	--------	------	-------------	-------	-------	-------	---