

Half screw connection - VC-M-KV-PG16(9-13) - 1853984

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Half screw connection Pg16, made of metal, consisting of rubber seal with one hole and one pressure screw, for type 1 housings, cable [mm] 9 - 13

Key commercial data

| | |
|------------------------|--|
| Packing unit | 1 |
| Minimum order quantity | 5 |
| Catalog page | Page 372 (PC-2009) |
| GTIN |  4 017918 146313 |
| Custom tariff number | 74153300 |
| Country of origin | POLAND |

Technical data

General data

| | |
|---------------------------------|--|
| Note | Adapter screw connections are available on request for large cable dimensions, from Pg16 to Pg21 and from Pg21 to Pg29 |
| Material, pressure screw | Nickel-plated brass |
| Seal material | TPE |
| Cable seal material | TPE |
| Wrench size, union nut | 24 mm |
| Thread type on seal side | PG16 |
| External cable diameter | 9 mm ... 13 mm |
| Degree of protection | IP67 |
| Ambient temperature (operation) | -40 °C ... 125 °C |

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 4.0 | 27141209 |
| eCl@ss 4.1 | 27141209 |
| eCl@ss 5.0 | 27149109 |
| eCl@ss 5.1 | 27149109 |
| eCl@ss 6.0 | 27149109 |
| eCl@ss 7.0 | 27149109 |

Half screw connection - VC-M-KV-PG16(9-13) - 1853984

Classifications

etim

| | |
|----------|----------|
| ETIM 2.0 | EC000441 |
| ETIM 3.0 | EC000441 |
| ETIM 4.0 | EC000441 |

unspsc

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11 | 31261502 |
| UNSPSC 12.01 | 31261502 |
| UNSPSC 13.2 | 31261502 |

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details



Accessories

Accessories

Assembly

Half screw connection - VC-M-KV-PG21- 0 - 1854983

Half screw connection made of metal with rubber seal without hole for sealing or for individual holes
