THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
DIFFUSION RESTREINTE AMP LIBRE A LA DIFFUSION
© COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED. TOUS DROITS RESERVES

LOC	DIST
F	00

REVISIONS

P	LTR REV	DESCRIPTION MODIFICATIONS	DATE	DWN DESS.	APVD APP.
	A	-1 REMPLACE PAR -4	17APR2001	JPP	JJR
	B	ADD VERSION WITHOUT RENAULT LOGO	12SEP2002	DB	JJR
	C	ADD NOTE RELATED OF CIRCUIT NUMBER	23OCT2006	DB	JJR





VERROU SECONDAIRE FERME
(SECONDARY LOCKING ACTIVATED)











REFERENCE MONTREE : 953657-4
(PN AS SHOWN : 953657-4)

REF. 1-953657-1 / 3-953657-1
ALVEOLE CENTRALE OBTUREE
(CENTRAL CAVITY BLOCKED UP)





			
0-953657-4	0-953657-2	0-953657-3	VERSION AVEC LOGO RENAULT *(VERSION WITH RENAULT LOGO)* 2
1-953657-1 1	-	-	
2-953657-1	2-953657-2	2-953657-3	VERSION SANS LOGO RENAULT *(VERSION WITHOUT RENAULT LOGO)* 2
3-953657-1 1	-	-	
NOIR / CODAGE1 *(BLACK / CODING1)*	BLEU / CODAGE2 *(BLUE / CODING2)*	GRIS / CODAGE3 *(GRAY / CODING3)*	COULEUR / CODAGE *(COLOR / CODING)*

CARACTERISTIQUES MECANIQUES *(MECHANICAL TEST)*	
EFFORT D'ACCOUPLEMENT *(MATING FORCE)*	< 80 N
EFFORT DE DESACCOUPLEMENT *(UNMATING FORCE)*	< 80 N
RETENTION DES CONTACTS *(CONTACT RETENTION FORCE)*	> 120 N
EFFORT D'INSERTION CONTACTS *(CONTACT INSERTION FORCE)*	< 25 N
CARACTERISTIQUES GENERALES *(GENERAL USAGE CONDITIONS)*	
CLASSE DE VIBRATION *(VIBRATION CLASS)*	1
CLASSE D'ETANCHEITE *(SEALING CLASS)*	2
CLASSE DE TEMPERATURE *(TEMPERATURE CLASS)*	2

VERSION SANS LOGO RENAULT *(VERSION WITHOUT RENAULT LOGO)* 2				VERSION AVEC LOGO RENAULT *(VERSION WITH RENAULT LOGO)* 2				
1	1	1	1	1	1	1	1	REMPLACE PAR -4 *(SUPERSEDED BY -4)*
1				1				
	1					1		
		1					1	
			1		1			
QTE COMPOSANT *(COMPONENT QTY)*								
X-953657-X								
3-/-1	2-/-3	2-/-2	2-/-1	1-/-1	-4	-3	-2	-1

COMPOSANTS ASSOCIES *(CONPONENT ASSOCIED)*		
P/N		DESIGNATION *(DESCRIPTION)*
828922-1		BOUCHON JPT *(JPT PLUG)*
/		2.8 GAMME 2 *(2.8 RANGE 2)*
/		2.8 GAMME 2 *(2.8 RANGE 2)*
/		2.8 GAMME 1 *(2.8 RANGE 1)*
/		2.8 GAMME 1 DOREE *(2.8 RANGE 1 GOLD PLATED)*
/		2.8 GAMME 1 *(2.8 RANGE 1)*

JAUNE (YELLOW)	PBT 20% FV (PBT GF20%)	VERROU *(SECONDARY LOCKING)*	2
NOIR (BLACK)	PBT 20% FV (PBT GF20%)	BOITIER 5 VOIES (ALVEOLE CENTRALE BOUCHEE) *(5 WAY HOUSING) (CENTRAL CAVITY BLOCKED UP)*	1
GRIS (GRAY)	PBT 20% FV (PBT GF20%)	BOITIER 5 VOIES *(5 WAY HOUSING)*	1
BLEU (BLUE)	PBT 20% FV (PBT GF20%)	BOITIER 5 VOIES *(5 WAY HOUSING)*	1
NOIR (BLACK)	PBT 20% FV (PBT GF20%)	BOITIER 5 VOIES *(5 WAY HOUSING)*	1
COULEUR *(COLOR)*	MATIERE *(MATERIAL)*	DESIGNATION *(DESCRIPTION)*	REP. *(ITEM)*

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION IT IS SUBJECTED TO CHANGE AND TOTAL CONTROL AND INTERESTING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.
CE PLAN EST UN DOCUMENT CONTROLE PAR AMP INCORPORATED IL EST SUSCEPTIBLE D'ETRE REVISE, CONTACTER LE SERVICE TECHNIQUE POUR SE PROCURER TOUTE LA DERNIERE REVISION

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED: TOLERANCES NON SPECIFIEES SUR DIMENSIONS DECIMALES: ±0.2 ANGLES ±1°

MATERIAL/MATIERE VOIR TABLEAU

FINISH/FINITION VOIR TABLEAU

DWN/DESSINE D. BANCE 30MAR2001
CHK/VERIFIE JP. PICAUD 30MAR2001
APVD/APPROUVE J.J. REVIL 30MAR2001
PRODUCT SPEC SPEC. PRODUIT 108-15221
APPLICATION SPEC SPEC. APPLICATION 411-15624
WEIGHT MASSE APPROX. 0.015Kg

CUSTOMER DRAWING /PLAN CLIENT UNIQUEMENT POUR REFERENCE

tyco Electronics
TYCO ELECTRONICS France SAS
BP 39, 95301 CERGY-PONTOISE Cedex

NAME TITRE: CONNECTEUR 5 VOIES POUR LANGUETTES 2.8 X 0.8 mm

SIZE FORMAT A1 | CAGE CODE 00779 | DRAWING NO No. PLAN C-953657 | RESTRICTED TO RESERVE A -

SCALE ECHELLE 2:1 | SHEET FEUILLE 1 OF DE 1 | REV C