



## Main

|                           |                          |
|---------------------------|--------------------------|
| Range of Product          | Harmony 9001SK           |
| Product or Component Type | Head for selector switch |
| Device short name         | 9001SK                   |
| Type of operator          | maintained               |
| Operator profile          | Black gloved hand knob   |

## Complementary

|                               |                        |
|-------------------------------|------------------------|
| Bezel material                | Plastic                |
| Mounting diameter             | 1.18 in (30 mm)        |
| Net Weight                    | 0.13 lb(US) (0.059 kg) |
| Shape of signaling unit head  | Round                  |
| Operator position information | 2 positions            |
| Contacts type and composition | Without contact block  |
| Mechanical durability         | 500000 cycles          |
| Device presentation           | Basic element          |

## Environment

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TC   |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)   |
| Electrical shock protection class     | Class II IEC 61140   |
| IP degree of protection               | IP66 IEC 60529   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X<br>NEMA 6                     |
| Standards                             | JIS C 852<br>EN/IEC 60947-5-4<br>UL 508<br>EN/IEC 60947-5-1<br>JIS C 4520<br>EN/IEC 60947-1<br>CSA C22.2 No 14 |
| Product Certifications                | NEMA<br>UL 508   |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6  |
| Shock resistance                      | 50 gn IEC 60068-2-27   |

## Ordering and shipping details

|                       |                    |
|-----------------------|--------------------|
| Category              | 21429-9001 SK,SKY  |
| Discount Schedule     | CS1                |
| GTIN                  | 785901043645       |
| Nbr. of units in pkg. | 1                  |
| Package weight(Lbs)   | 3.20 oz (90.719 g) |
| Returnability         | No                 |
| Country of origin     | MX                 |

## Packing Units

|                        |                      |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE                  |
| Package 1 Height       | 7.62 in (19.355 cm)  |
| Package 1 width        | 3.00 in (7.62 cm)    |
| Package 1 Length       | 19.35 in (49.161 cm) |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|