

product type designation

product description

IE FC M12 Cable Connector PRO (PROFINET)

M12 connector with socket insert with high protection class, 8-pole, X-coded

IE FC M12 Cable Connector PRO 4x 2 M12 plug-in connectors that can be assembled in the field (X-coded) 8-pole; metal enclosure; FC quick-connect technology; female contact insert; 1 pack = 1 unit.



suitability for use

For connecting electrical cables to SCALANCE W (M12 gigabit interface) for fast assembly with the FastConnect system

transfer rate

transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10000 Mbit/s

interfaces

number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

8
1

type of electrical connection

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

integrated cut-and-clamp contacts for 8-wire TP FC installation cable AWG24
M12 connector (X-coded)

type of electrical connection / FastConnect

Yes

mechanical data

material / of the enclosure

metal

locking mechanism design

Screwed joint

tightening torque / for M12 round connector / maximum

0.6 N·m

design, dimensions and weights

type of cable outlet

180° cable outlet

width

16.8 mm

height

16.8 mm

depth

49 mm

net weight

40 g

connectable cable cross-section

6.5 ... 8 mm

connectable conductor cross-section

0.21 ... 0.33 mm²

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +85 °C
-40 ... +85 °C
-40 ... +85 °C

chemical resistance

- to water

resistant

protection class IP

IP65/67

product features, product functions, product components / general

product feature

- PoE capability

Yes

<ul style="list-style-type: none"> • PoE+capability • silicon-free 	Yes
product component	Yes
<ul style="list-style-type: none"> • strain relief 	Yes
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • RoHS conformity • UL approval • cULus approval • railway application in accordance with EN 50155 • fire protection in accordance with EN 45545-2 	Yes
standard for structured cabling	Cat6A
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	6/30/2021 