


**Series: Embedded Antenna** 

#### TECHNICAL DATA SHEET

Description: 5GHz WiFi SMT Antenna

PART NUMBER: W3713



### Features:

• Frequency: 4.9-6GHz

Gain: 4.5dBi

Size: 10.5 x 3.2 x 2.4 mm

SMT compatible

Packing: Tape&Reel

· RoHS compliant

· Mirror image pair for this antenna is W3714

## **Applications:**

WiFi, ISM 5GHz

DSRC 5.925GHz

Tablets, Notebooks

IoT and M2M devices

Portable Electronics

Security, Transportation

All dimensions are in mm / inches

Issue: 1812

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:



Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

**Series: Embedded Antenna** 

## **ELECTRICAL SPECIFICATIONS**

Frequency 4.9-6GHz

Nominal Impedance  $50\Omega$ 

VSWR 2:1

Peak Gain 4.5dBi +/- 1 dB

Radiation Pattern Omni

Polarization: Linear

Power withstanding 5W



Description: 5GHz WiFi SMT Antenna

**Series: Embedded Antenna** 

**PART NUMBER: W3713** 

MECHANICAL SPECIFICATIONS					
Material	Phosphor bronze				
Thickness	0.2	mm			
Weight	0.1	g			
Overall Length	10.5(0.41)	mm(inch)			
Fixing system	SMT				

## **ENVIRONMENTAL SPECIFICATIONS**

Operating temperature

-40/+85 ° C







Description: 5GHz WiFi SMT Antenna


**PART NUMBER: W3713** 

**Series: Embedded Antenna** 

## **MECHANICAL DRAWING**









Description: 5GHz WiFi SMT Antenna


PART NUMBER: W3713

Series: Embedded Antenna


## **OTHER SPECIFICATIONS**

## **PCB LAYOUT:**

1, PCB material, FR4, size, 76.2X76.2X0.8mm



# Clearance area (Top)



Issue: 1812




Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 


**Series: Embedded Antenna** 

## **OTHER SPECIFICATIONS**

# 3, Clearance area (Bottom)



## 4, PCB Features








Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 


**Series: Embedded Antenna** 

## **OTHER SPECIFICATIONS**

# 3, Antenna on test PCB



Reserved for W3714





Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

**Series: Embedded Antenna** 

## **OTHER SPECIFICATIONS**

## Recommendation for reflow soldering process

Printing stencil thickness 0,15 - 0,25 mm is recommended for the solder paste. The maximum soldering temperature should not exceed 260°C. The temperature profile recommendations for reflow soldering process is presented in the Figures 1 and 2. The reflow profile presented in figure 1 describes minimum reflow temperatures. The reflow profile presented in figure 2 describes maximum reflow temperatures. located at the center of the coverage area.

	Method of heat transfer	Controlled hot air convection
1	Average temperature gradient in preheating	2.5 °C/s
2	Soak time	2-3 minutes
3	Max temperature gradient in reflow	3 °C/s
4	Time above 217 °C	Max 30 sec
5	Peak temperature in reflow	230 ℃ for 10 seconds
6	Temperature gradient in cooling	Max -5 °C/s




Figure 1. Minimum temperature profile recommendation for reflow soldering process





Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

## Series: Embedded Antenna

## **OTHER SPECIFICATIONS**

	Method of heat transfer	Controlled hot air convection
1	Average temperature gradient in preheating	2.5 °C/s
2	Soak time	2-3 minutes
3	Max temperature gradient in reflow	3 °C/s
4	Time above 217 °C	Max 60 sec
5	Time above 230 °C	Max 50 sec
6	Time above 250 °C	Max 10 sec
7	Peak temperature in reflow	260 °C for 5 seconds
8	Temperature gradient in cooling	Max -5 °C/s




Figure 2. Maximum temperature profile recommendation for reflow soldering process






Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

**Series: Embedded Antenna** 










Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

Series: Embedded Antenna

## **CHARTS**

# Efficiency(%)







Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

Series: Embedded Antenna

### **CHARTS**

# Peak Gain (dBi)








Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

## **Series: Embedded Antenna**

## **CHARTS**

# Free Space Radiation Pattern









Description: 5GHz WiFi SMT Antenna

**PART NUMBER: W3713** 

# **Series: Embedded Antenna**

## **PACKAGING**

Tape and Reel packing: 3000PCS/Tape and Reel 6000PCS/ Carton box

Tape Width: 24mm

Tape Material: Polystyrene



