

# US-Lasers: 660nm-5mW - Red Laser Diode

[Back to Laser Diodes](#)

## RED LASER DIODE DATA SHEETS ABSOLUTE MAXIMUM RATINGS - (Tc=25 °C)

TECHNICAL DATA		Pin Out Diagram - Style A	
Visible laser diode light output	660nm	1	laser cathode
Optical power output	5mW CW	2	common case
Package Type	5.6mm	3	monitor diode anode
Built-in photo diode for monitoring laser output			

Items	Symbols	Values	Unit
Optical output power	Po	5	mW
Laser diode reverse voltage	V	2	V
Photo diode reverse voltage	V	30	V
Operating temperature	Topr	-10 ~ +60	°C
Storage temperature	Tstg	-40 ~ +85	°C

## OPTICAL and ELECTRICAL CHARACTERISTICS - (Tc=25 °C)

Items	Symbols	Min.	Typ.	Max.	Unit	Test Condition		
Optical output power	Po	-	5	-	mW	-		
Threshold current	Ith	-	20	40	mA	-		
Operating current	Iop	-	40	60	mA	Po=5mW		
Operating voltage	Vop	-	2.7	-	V	Po=5mW		
Lasing wavelength		655	660	665	nm	Po=5mW		
Beam divergence		-	5	11	deg	Po=5mW		
Beam divergence		-	25	37	deg	Po=5mW		
Monitor current	Is	-	10	20	uA	Po=5mW		
Astigmatism	As	-	11	-	um	Po=5mW		
MTTF		10000 hrs				Po=5mW		
Emitter Size	10 x 60 Microns - Emitter Distance to Cap Lens = 0.3mm							
Structure	Index Guided							