


Data sheet | Item number: 289-449

Interface module; with solder pin; Male connector; 50-pole; Mating connector with solder connection; Vertical mounting; PCB terminal blocks, double-row; with mounting feet; 2,50 mm²



www.wago.com/289-449



Data

Electrical data

Operating voltage	≤30 VAC; ≤50 VDC
Nominal current	1 A

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Contact resistance (max.)	30 mΩ
---------------------------	-------

Safety and protection

Rated voltage	50 V
Rated surge voltage	0.8 kV
Pollution degree	2
Protection type	IP00; Notice! Live parts can be easily touched! Protection against direct contact must be provided by the equipment manufacturer, e.g., using a WAGO 709 Series Cover (see "Accessories") or a similar cover. The installation guidelines must be observed for each individual application.
Insulation type	Basic insulation

Connection data

Performance level	2 / 200 mating cycles
Strain relief	UNC 4-40 stud bolt

Connection 1

Connector	D-subminiature male connector
Pole number 1	50
Connection type 1	System
Note (conductor cross-section)	12 AWG: THHN, THWN
Mating direction	vertical

Connection 2

Design 2	PCB terminal blocks (double-row)
Pole number 2	50
Connection type 2	Field
Connection technology 2	CAGE CLAMP®
WAGO connector 2	WAGO 236 Series
Solid conductor 2	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Fine-stranded conductor 2	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Strip length 2	5 ... 6 mm / 0.2 ... 0.24 inches

Physical data

Width	157 mm / 6.181 inches
-------	-----------------------

Subject to changes. Please also observe the further product documentation!



Height	63.5 mm / 2.5 inches
Depth from upper-edge of DIN-rail	19 mm / 0.748 inches

Mechanical Data

Mounting type	DIN-35 rail
Housing design	PCB with mounting feet

Material Data

Contact material (connector)	Au over Ni
Fire load	0.081 MJ
Weight	98.7 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
Ambient temperature (storage)	-40 ... +70 °C
Relative humidity	85% (non-condensing)

Standards and specifications

Standards/specifications	EN 61010-2-201
--------------------------	----------------

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-14-11-52
eCl@ss 9.0	27-14-11-52
ETIM 8.0	EC002780
ETIM 7.0	EC002780
PU (SPU)	5 (1) pcs
Packaging type	box
Country of origin	DE
GTIN	4045454599423
Customs tariff number	85366990990

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption

Subject to changes. Please also observe the further product documentation!



RoHS Exemption	6(c)
SCIP notification number (Austria)	f37bd52d-cd1e-4a17-8b6f-4b4aab35e041
SCIP notification number (Belgium)	8f5f0157-2460-42b1-8f0e-e973920c5ac9
SCIP notification number (Bulgaria)	a1fe57e8-c7e2-4083-ad37-f47ff4a9b3d0
SCIP notification number (Czech Republic)	3115decb-3499-4b66-a6c3-d2f3c8ad1a7d
SCIP notification number (Denmark)	3d5644c9-b42c-41b9-b0c8-bad9387248b9
SCIP notification number (Finland)	02548901-7b45-497a-accb-3a0379fbeba7
SCIP notification number (France)	0b73c2fc-5523-44c2-8420-28a35cc9775b
SCIP notification number (Germany)	1564835a-eec6-4b59-adf1-f87a59435c4a
SCIP notification number (Hungary)	07e198eb-8d32-4ba2-b773-df9dffa3cd08
SCIP notification number (Italy)	fb299edc-3755-44b5-8273-50a52b8b570f
SCIP notification number (Netherlands)	c5fc6a9b-d5ea-447b-a257-26191caee825
SCIP notification number (Poland)	50d0a6f1-89ad-4ce5-bc92-c2911bd5eada
SCIP notification number (Romania)	c4d4ffbd-ec01-4af8-a497-6d5498258bc7
SCIP notification number (Sweden)	e806ae4d-101d-44aa-9e74-645a0094d4fc

Optional accessories

Tool

Operating tool		
	Item no.: 210-720 Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured	www.wago.com/210-720

Mounting

Cover carrier		
	Item no.: 709-167 Cover carrier; Type 1; incl. fixing/retaining screws and knurled nut; suitable for 279 to 282 and 880 Series rail-mounted terminal blocks; suitable for 264 Series miniature rail-mounted terminal blocks; suitable for 270 Series sensor and actuator terminal blocks; gray	www.wago.com/709-167
Cover		
	Item no.: 709-153 Cover; Type 1; suitable for cover carrier, type 1; 1 m long; transparent	www.wago.com/709-153

Downloads

Documentation

Bid Text

289-449	2015 年2月6日	doc	Download
doc - Datei		26.6 kB	

Instruction Leaflet

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



pdf
1.3 MB

Download

Additional Information

Disposal and Recycling	V 1.1.0	pdf	Download
Electrical and electronic equipment, Batteries, Packaging	2022 年8月18 日	2.2 MB	

CAD/CAE-Data

CAE data

EPLAN Data Portal 289-449	URL	Download
---------------------------	-----	----------

WSCAD Universe 289-449	URL	Download
------------------------	-----	----------

ZUKEN Portal 289-449	URL	Download
----------------------	-----	----------

CAD data

2D/3D Models 289-449	URL	Download
----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 289-449	URL	Download
------------------------------------------	-----	----------

Interface module; with solder pin; Male connector; 50-pole; Mating connector with solder connection; Vertical mounting; PCB terminal blocks, double-row; with mounting feet; 2,50 mm²

Installation Notes

Conductor termination

Subject to changes. Please also observe the further product documentation!



Conductor termination – screwdriver actuation parallel to conductor entry



Conductor termination – screwdriver actuation perpendicular to conductor entry

Subject to changes. Please also observe the further product documentation!