

Datasheet for 76650-0153

General Information				
Part Number:	76650-0153			
Manufacturer:	Molex / Waldom			
Title:	Solderless Terminal Kit			
Description:	Nylon Insulated .250" Tab Size Quick Disconnect, Quick Disconnect Adaptor and Coupler			
Product Family:	Quick Disconnects			
Certificates:	(Molex Parts within this kit) - EU RoHS Compliant			
Country of Origin:	Kit assembled in U.S.A.			
Specifications				
Design				
Configuration:	Wire-to-Wire / Solderless Terminals			
Tab Size:	.250"			
Connector Type:	Male and Female			
Insulation:	Nylon			
Current Rating:	(3-15) Amps - Dependant on Wire Gauge			
Voltage:	300 Volts			
Wire size:	(22-18), (16-14), (14-12) and (12-10) AWG			
Product Highlights				

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade. Quick Disconnects (QDs) are female terminals that mate with male tab terminals, tab adapters, and terminal blocks fitted with male tabs.

Features and Benefits

Applications

1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



• MRO (Maintenance Repair and Operations)

Datasheet for 76650-0153

Consumer applicationsPower applications

Motor applications

- Color-coded insulator allows easy indentification of terminal size and wire gauge.
- Avikrimp provides a metal insulation support sleeve for superior strain relief
- These fulfill the double crimp (support) requirements of VDE and other DIN specifications
- Make two .250" x .032" male tabs from one male tab when an add-on circuit is needed
- Converts one Power Block 1/4" (female) to two male tabs 10 deg. bend-up; 120 deg. bend-back
- Splices two female 1/4" quick connects

Bill of Materials for Part No. 76650-0153

Molex Part No.	Country of Origin	Description	Quantity in Kit
19019-0012	USA	.250 x .032 Nylon Female Quick Disconnects (22-18) AWG	25
19019-0031	USA	.250 x .032 Nylon Female Quick Disconnects (16-14) AWG	25
19019-0052	USA	.250 x .032 Nylon Female Quick Disconnects (14-12) AWG	25
19019-0037	USA	.250 x .032 Nylon Female Quick Disconnects (12-10) AWG	25
19043-0001	USA	.250 x .032 Double Male / Single Female Quick Disconnect Adapter	10
19043-0010	Taiwan	.250 x .032 Three Way Quick Disconnect Adapter	10
19163-0178	Taiwan	.250 x .032 Double Male Quick Disconnect Insulated Coupler	5

Recommended Molex Tool(s) for Part No. 76650-0153*

Molex Part No.	Country of Origin	Description
64001-0200 *	USA	Hand Crimp Tool (RHT-1991) / (22-18) AWG
64001-1700 *	USA	Hand Crimp Tool (RHT-5757) / (22-18) AWG
64001-1800 *	USA	Hand Crimp Tool (RHT-5759) / (14-12) AWG
64001-2000 *	USA	Hand Crimp Tool (RHT-5758) / (16-14) AWG
64001-7300 *	USA	Hand Crimp Tool (RHT-2210) / (12-10) AWG

*Tool(s) not included in kit. Tool(s) ordered separately.