

https://www.phoenixcontact.com/us/products/2203393



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Stand for mounting the UCS housing; height: 47 mm; material: polyamide; color: black, similar to RAL 9005; wall mounting option is integrated, snaps into the screw holes of the housing



Your advantages

- · Practical customization options
- Tool-free snap-in principle enables easy mounting on the device panel
- · Flexible mounting options for the control cabinet and use in the field
- · Can be adapted to suit the application, thanks to identical receptacles in the housing
- Different colors for high recognition value inside and outside the control cabinet

Commercial data

Item number	2203393
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AC03
Product key	ACFCAZ
GTIN	4055626462516
Weight per piece (including packing)	33.2 g
Weight per piece (excluding packing)	33.2 g
Customs tariff number	39269097
Country of origin	DE



https://www.phoenixcontact.com/us/products/2203393



Technical data

Notes

General	Refer to the data sheet for the range in the download area.
General	The UCS PED stand has drill holes that are also suitable for wall mounting. Recommended screws for wall mounting: S5 dowel, ø 4.0 mm screw.

Product properties

Product type	Mounting material
Housing type	Universal housings
Ventilation openings present	no
Housing series	UCS

Dimensions

Width	90 mm
Height	37.5 mm
Depth	19.2 mm
Diameter mounting hole	4 mm

Material specifications

Color	black (9005)
Flammability rating according to UL 94	V0
CTI according to IEC 60112	600
Insulating material	PA
Surface characteristics	untreated
Housing material	Polyamide

Environmental and real-life conditions

Ambient conditions

Max. IP code to attain	IP40
Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C 55 °C
Ambient temperature (assembly)	-5 °C 100 °C
Relative humidity (storage/transport)	80 %

Mounting

Mounting type	Snap in
Mounting position	Wall mounting

Packaging specifications

Type of packaging PE bag	
--------------------------	--



https://www.phoenixcontact.com/us/products/2203393



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2203393



UL RecognizedApproval ID: FILE E 240868

Aug 31, 2023, 4:24 PM Page 3 (5)



https://www.phoenixcontact.com/us/products/2203393



Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27182702
	ECLASS-13.0	27190605
ETIM		
	ETIM 8.0	EC001031
UN	ISPSC	

31261500

2203393

https://www.phoenixcontact.com/us/products/2203393



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com