_	Mallory Sonalert Products, Inc.				Part #: JT028-RYG-CEL		
Sales Outline Drawing				Revision: C			
pecifications:							
Stack Number:	1	2	3				
LED Color:	RED	YELLOW	GREEN				
Connection Wires:	Red and Brown	Yellow and Brown	Green and Brown				
LED Current Draw:	<50 mA	<60 mA	<40 mA				
Rated Voltage:	100		24 VAC/DC	!			
Operating Voltage:			20-28 VAC/D0	3			
Sound Level Category:	Loud	Loud	Loud			Loud	
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.	5775)		for 5 sec then 0.1s beep up	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wire wire connected to Gray wire	oon/Vollow black and t		Gray wires; Orange and Pur	
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max		40mA Max.		
Loudness @ 1m:			80-85 dB(A) Ty				
Frequency:			2000 ± 500 H				
Total Max Current:		<190m	A with all LED's and so		rking		
Operating Temperature:			-25° ~ +60°C		<u> </u>		
Lens Color:	Opaque White						
Material:	ABS FR15U						
Mounting Method:	Stainless Steel Pole - Black						
Weight Typical (g):	730						
NEMA 12:	Approved						
Options:			Please contact fac	ctorv.			
6.7 [169.8]	GREEN	NUMBER D898600	10309594			·	
		NUMBER D898600	10309594	G <i>é</i>	NSKET	48° wire	
	GREEN		10309594	Gέ	SKET	ROHS Complia	
RED	GREEN	-19.6 [497.6]	Ø 0.	20 [Ø5.2] places	Ø0.57 [Ø1 for wir	48' wire 4.6] es	
2.4 [61] ————————————————————————————————————	T STACK COLOR WIR	-19.6 [497.6] RE TO POWER AND BE	#10 or 5m screws for mounting 10.39 [9 0.95 [3	20 [\$5.2] places 91 91 MEUNT DIAGR	0.57 [ø1 for wir 2.04 0.95 [2	48' wire 4.6] es	