

3-3/4 digits 3999 Counts Autorange Compact Digital Multimeter

Item: MT-1232

- Complies with CE CATIII safety standard
- 3 ft drop protection
- 3 3/4 digits 3999 counts
- Large and easy to read display panel
- Overload and mis-use protection
- Auto / manual both range

Extra functions: Relative reference, LED backlight, data hold, auto power off, low battery indication.



Digits	3 3/4 digits 3999 counts
Accuracy	0.5% best accuracy
DCV	400mV/4V/40V/400V ±(0.5%+4d), 600V ±(1.0%+4d)
ACV	4V/40V/400V ±(0.8%+6d), 600V ±(1.0%+6d)
DCA	400µA/4000µA ±(1.0%+10d), 40mA/400mA ±(1.0%+10d), 10A ±(1.2%+10d)
ACA	400µA/4000µA ±(1.5%+10d), 40mA/400mA ±(1.5%+10d), 10A ±(2.5%+15d)
Resistance	400Ω ±(0.8%+5d) 4k/40k/400K ±(0.8%+4d), 4MΩ ±(0.8%+4d) 40MΩ (1.2%+10d)
Frequency	1/10/100Hz ±(0.5%+10d), 1K/10K/100KHz ±(0.5%+10d), 1/10MHz ±(0.5%+10d)
Capacitance	4nF ±(0.5%+9d), 40nF/400nF/4µF/40µF ±(3.5%+8d), 100µF ±(5.0%+8d)
Temperature	(-20C~1000C) < 400C±(1.0+5d), (-20C~1000C) >= 400C±(1.5+15d)
Fuse	10A/250V
Power source	1.5V AA x 2 (not included)
Size (HXWXD)mm	5.8 x 3.1 x 1.3 in.

Order Today! SalesSupport@EclipseTools.com

Eclipse Enterprises, Inc. ● Tel: 804.561.2610 ● Fax: 804.561.2642

13302 Chula Road, Amelia Court House, VA 23002 ● EclipseTools.com