



**SAKS 1**  
Neon Lamp



Single Level  
5 x 20 mm Fuse

**SAKS 1**  
LED



Single Level  
5 x 20 mm Fuse

**Terminal Block Selection Data**

Available Options	Version	↵	↵	↵	↵
	Beige Wernid				
	Beige PA				
	KrG				
	24 VDC			0371420000	0225820000
	24 VDC Hinge +				
	24 VDC Hinge -				
	24 VAC				1111320000
	24 VAC/DC		0173220000		
	48 VDC				
	48 VAC				
	48 VAC/DC		0378920000		
	40-50 VAC				0214020000
	40-50 VDC				
	100 VDC				
	110 VAC		0385320000		
	120 VAC/DC				
	220 VDC				
	220 VAC				
	220 VAC/DC		0306120000	0199920000	

**Dimensions**

Width / Length / Height mm (in.)	for TS 32	↵	13/54/61 (.51/2.13/2.4)	13/54/61 (.51/2.13/2.4)
	for TS 35	↵	13/54/54 (.51/2.13/2.13)	13/54/54 (.51/ 2.13/2.13)
Insulation stripping length	mm (in.)		12 (.47)	12 (.47)

**Technical Data**

Rated voltage / rated current / wire size	UL	V* / 6 A / #22...10 AWG	V* / 6 A / #22...10 AWG
	CSA	V* / 10 A / #26...10 AWG	V* / 10 A / #26...10 AWG
	VDE	220 V / 110 V / 10 A / 10 mm <sup>2</sup>	24 V / 10 A / 10 mm <sup>2</sup>
Torque	Nm (lb. in.)	1.2 (26)	1.2 (26)
Clamping screw	M	4	4

**Selected Accessory Data<sup>‡</sup>**

End Plate (thickness mm)	Type	Part No.	Type	Part No.	
PA					
	AP (2.5)	0191320000	AP (2.5)	0191320000	
Partition (thickness mm)					
	HP	TW (2.0) ↵	TW (2.0) ↵	0607000000	
<b>G Fuse Cartridges, 5 x 20 mm</b>					
Numbers indicate rated current in Amps.  Rated voltage: 250 VAC Switching capacity: 1500 A (at 250 V, 50 Hz, cos φ = 0.7)	0.10 rapid-blow	0430300000	0430300000		
	0.20 rapid-blow	0430400000	0430400000		
	0.25 rapid-blow	0430500000	0430500000		
	0.50 rapid-blow	0430600000	0430600000		
	1.0 rapid blow	0430700000	0430700000		
	1.6 rapid-blow	0430800000	0430800000		
	2.0 rapid-blow	0430900000	0430900000		
	2.5 rapid-blow	0431000000	0431000000		
	3.15 rapid-blow	0431100000	0431100000		
	4.0 rapid-blow	0431200000	0431200000		
	5.0 rapid-blow	0431300000	0431300000		
	6.3 rapid-blow	0431400000	0431400000		
	Solid brass slug	0446100000	0446100000		
Hollow brass slug					
<b>Fuse Cap / Disconnect Lever (spare)</b>					
Fuse cap	SK (5 x 20)	0282100000	SK (5 x 20)	0282100000	
Spare lever					
Spare red lever					
<b>Marking Tags</b>					
Note: Part numbers are shown for a single card of pre-printed tags numbered 1-50.	Consecutive horizontal	DEK 5/5	0473460001	DEK 5/5	0473460001
	Consecutive vertical	DEK 5/5	0473560001	DEK 5/5	0473560001

RAIL MOUNTED TERMINAL BLOCKS: SAK-SERIES

<sup>‡</sup>See Accessories section for additional information.  
\*Voltage limit dependent on the version selected.