

Engineering Product Design

Product Construction 3 Conductor Cable Shielded and Jacketed

Controlled Customer Copy B.W.B. **GERMANY**

Product Description

Rev

VG 95218 T028 C037


2

Designer John Ribbons **Date** 16/07/2019 **Product Manager** Mark Johnstone

Date 16/07/2019

Component Identification

Cross-Section



Components

ID	Туре	Quantity	Part Description (Components refer to issue in effect at date of issue of this EPD)
Α	Wire	1	VG 95218 T020 E100
В	Wire	1	VG 95218 T020 E101
С	Wire	1	VG 95218 T020 E106

Component Identification

Key	Wire/Core Colour(s)	Wire/Core Number(s)	Jacket/Wrap Colour(s)	Jacket/Wrap Number
A1	0			
B1	1			
C1	6			

Cabling

Layer No	Quantity	Description	Nominal O.D. mm
Layer 1	1	VG 95218-T020-E100	
	1	VG 95218-T020-E101	
	1	VG 95218-T020-E106	
	3	Fillers	5.5

Tyco Electronics UK Ltd. Faraday Road, Dorcan Swindon SN3 5HH Tel: (01793) 528171 Website: www.te.com

TE Connectivity is a trading name of Tyco Electronics UK Ltd, which is registered in England and Wales, number 550926. Registered office: Faraday Road, Dorcan, Swindon, SN3 5HH

This drawing and the information set forth hereon are the property of Tyco Electronics UK Ltd, and are to be held in trust and confidence. Publication, duplication, disclosure or use for any purpose not expressly authorised in writing by Tyco Electronics UK Ltd is prohibited.

© 2019 Tyco Electronics UK Limited. A TE Connectivity Ltd company. All Rights Reserved.



Engineering Product Design

Product Construction 3 Conductor Cable Shielded and Jacketed Controlled Customer Copy B.W.B. GERMANY **Product Description**

Rev

VG 95218 T028 C037

2

_				
()		т	Δ	r
v	u	u	◡	

Layer Type	Description	Nominal O.D. mm
Wrap:	Polyester	5.6
Shield: Optimised Braid	Tin Plated Copper	6.2
Jacket: Extrusion 1	Zerohal® - Black Marked 'Raychem - VG 95218 T028 C037 - K1010 - VDE Reg.Nr.	7.9 ±0.4
	7095 - LMGSGO - (3x2,5)'	Min Wall - 0.70mm

Cable Characteristics

Maximum Weight	145 (kg/km)
Maximum Surface Transfer Impedance	100 milli Ohms/metre @ 30MHz
	30 milli Ohms/metre @ 10MHz

This cable is RoHS Compliant

Specifications

VG 95218 Part 28 Type C

Notes

Braid - AWG36 Internal Reference - EPD81502B

Lengths

Unless otherwise specified on your order this cable may be supplied in the following maximum number of continuous lengths with no single length less than 25m:

Order Quantity (m) + One other length 100