

## ZV50E50A01

**ZV Series, Subminiature Basic Switch, SPDT, 6(2)A 250 Vac, 6 A, Pin Plunger Actuator, PCB Right Angle Termination**

*Due to regional agency approval requirements, some products may not be available in your area. Please contact your regional Honeywell office regarding your product of choice.*

### Features

- ? Subminiature: 10,6 mm H x 6,4 mm W x 19,8 mm L [0.42 in H x 0.25 in W x 0.78 in L]
- ? Choice of low energy or power duty electrical ratings (gold plated or silver contacts)
- ? Single pole double throw (SPDT) circuitry or single pole single throw (SPST) circuitry available
- ? Choice of 0.1 or 6 A ratings
- ? Choice of actuation, termination and operating characteristics
- ? Polyamide (nylon) housing material

### Typical Applications

- ? Appliances
- ? Vending machines
- ? Timing devices
- ? Office equipment
- ? Computer/business equipment
- ? Test instruments
- ? Medical/dental equipment
- ? Communications equipment
- ? HVAC equipment
- ? Manually operated devices
- ? Valves

### Description

ZV Series Subminiature Basic Switches are used for simple or precision ON/OFF application needs. These switches combine small size and light weight with ample electrical capacity, low cost and long life.

## ZV50E50A01

**ZV Series, Subminiature Basic Switch, SPDT, 6(2)A 250 Vac, 6 A, Pin Plunger Actuator, PCB Right Angle Termination**

Product Specifications	
Switch Type	Subminiature 10,6 mm H x 6,4 mm W x 19,8 mm L [0.42 in H x 0.25 in W x 0.78 in L]
Sealed	No
Ampere Rating	6 A
Circuitry	Single Pole Double Throw (SPDT)
Actuator	Pin Plunger
Termination	PCB Right Angle
Operating Temperature Range	-25 °C to 85 °C [ -13 °C to 185 °C]
Voltage	6(2)A 250 Vac
Approvals	CE/cUL/UL/ENEC
Contact Type	Silver Cadmium Oxide
Operating Force (O.F.)	1,43 N [5.15 oz] max.
Release Force (R.F.)	0,34 N [1.23 oz] min.
Pretravel (P.T.)	1,1 mm [0.043 in] max.
Overtravel (O.T.)	0,4 mm [0.016 in] min.
Differential Travel (D.T.)	0,2 mm [0.008 in] max.
Operating Position (O.P.)	11,4 mm ± 0,3 mm [0.449 in ± 0.012 in]
Free Position (F.P.)	12,8 mm [0.504 in] max.
Housing Material	Polyamide (Nylon)
Humidity	Max. 85% RH at 40 °C [104 ° F]
High Temperature	85 °C [185 °F]
Mechanical Service Life	Min. 5,000,000 operations
Dielectric Strength	750 Vac (50 Hz to 60 Hz) between contacts and 1,250 Vac (50 Hz to 60 Hz) between terminals and ground, for one minute
Electrical Service Life	Min. 10,000 on resistive and motor load current, 6(2)A 250 Vac
Electrical Operating Frequency	Max. 400 operations per minute
CE mark	61058 - 1
UL File #	E12252
C-UL File #	E12252
Agency Approvals and Standards	1054
Mounting Screw Size	2,3 mm [0.091 in] Flat fillister head
Mounting Centers	9,5 mm [0.37 in]
Maximum Tightening Torque	0,31 N m [2.7 in lb]
Availability	Global
UNSPSC Code	30211905
UNSPSC Commodity	30211905 Snap switches
Prod Code (Stock No.)	FBY0010
Series Name	ZV Series

## ZV50E50A01

**ZV Series, Subminiature Basic Switch, SPDT, 6(2)A 250 Vac, 6 A, Pin Plunger Actuator, PCB Right Angle Termination**

<p><b>⚠ WARNING</b>  <b>PERSONAL INJURY</b>            DO NOT USE these products as safety or emergency stop devices, or in any other application where failure of the product could result in personal injury.</p> <p><b>Failure to comply with these instructions could result in death or serious injury.</b></p>
--

<p><b>⚠ WARNING</b>  <b>MISUSE OF DOCUMENTATION</b></p> <ul style="list-style-type: none"> <li>? The information presented in this product sheet (or catalog) is for reference only. DO NOT USE this document as product installation information.</li> <li>? Complete installation, operation and maintenance information is provided in the instructions supplied with each product.</li> </ul> <p><b>Failure to comply with these instructions could result in death or serious injury.</b></p>
--