



Main

| | |
|---------------------------|-------------------|
| Range of Product | 9007 |
| Series name | Heavy duty |
| Product or Component Type | Snap limit switch |
| Device short name | 9007AO/CO |
| Body type | Fixed |

Complementary

| | |
|--|---|
| Mounting Mode | - |
| Operator profile | Plunger head |
| Material | Metal |
| Body Material | Cast zinc |
| Operator material | Cast zinc |
| Fixing Mode | By the body |
| Movement of operating head | Linear |
| Type of operator | Spring return roller lever plunger metal RH bracket + 0.47" roller |
| Switch actuation | By 30° cam |
| Type of approach | Traverse approach, 2 directions |
| Electrical connection | 1...2 6 binder head screw terminals AWG 22...AWG 14) |
| Number of poles | 2 |
| Contacts type and composition | 2(NC-NO) DPDT-DB |
| Contact form | Form ZZ |
| Contact operation | Snap action |
| Number of steps | 1 |
| Contacts material | Silver contacts |
| Positive opening | Without |
| Terminals description ISO n°1 | (3-4)NO (7-8)NO (1-2)NC (5-6)NC |
| Minimum force for tripping | 0.5 lbf |
| Maximum force for tripping | 0.5 lbf |
| [Ie] rated operational current | 0.6 A 600 V AC, B600 NEMA rating designation 0.75 A 480 V AC, B600 NEMA rating designation 1.5 A 240 V AC, B600 NEMA rating designation 3 A 120 V AC, B600 NEMA rating designation 0.1 A 250 V DC 0.2 A 125 V DC |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 600 V 3)UL 508 contact block 600 VCSA C22.2 No 14 contact block |
| Width | 0.95 in (24.13 mm) |
| Height | 2.5 in (63.50 mm) |
| Depth | 2.54 in (64.52 mm) |
| Net Weight | 1.5 lb(US) (0.68 kg) |

Environment

| | |
|---------------------------------------|------------------------------|
| NEMA degree of protection | NEMA 1 Nema type 250 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Ambient air temperature for operation | -20...185 °F (-29...85 °C) |
| Ambient Air Temperature for Storage | -20...185 °F (-29...85 °C) |

Ordering and shipping details

| | |
|-----------------------|------------------------------|
| Category | 21492 - 9007 C SNAP SWITCHES |
| Discount Schedule | DS1 |
| GTIN | 785901157908 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 24.00 oz (680.389 g) |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 5.30 in (13.462 cm) |
| Package 1 width | 7.00 in (17.78 cm) |
| Package 1 Length | 7.60 in (19.304 cm) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|