

Temperature Compensated Zener Reference Diode Series

1N821UR thru 1N829AUR & 1N821UR-1 thru 1N829UR-1



Features


- 1N821UR-1, 1N823UR-1, 1N825UR-1, 1N827UR-1 and 1N829UR-1 and A versions available in JAN, JANTX, JANTXV, JANS
- Metallurgically Bonded, Double Plug Construction

Maximum Ratings

Operating & Storage Temperature: -65°C to +175°C

DC Power Dissipation: 500mW @ +50°C

Power Derating: 4 mW / °C above +50°C



REVERSE LEAKAGE CURRENT

$$I_R = 2 \mu A @ 25^\circ C \text{ \& } V_R = 3 Vdc$$

Electrical Specifications @ +25 °C (Unless Otherwise Specified)


JEDEC TYPE Number (Note 1)	Normal Zener Voltage $V_Z @ I_{ZT}$	Zener Test Current I_{ZT}	Maximum Zener Impedance (Note 1) Z_{ZT}	Voltage Temperature Stability ${}^3V_{ZT}$ -55° to +100°C (Note 2)	Effective Temperature Coefficient
	Volts	mA	Ohms	mV	%/°C
1N821UR	5.9–6.5	7.5	15	96	0.01
1N821AUR	5.9–6.5	7.5	10	96	0.01
1N822UR †	5.9–6.5	7.5	15	96	0.01
1N823UR	5.9–6.5	7.5	15	48	0.005
1N823AUR	5.9–6.5	7.5	10	48	0.005
1N824UR †	5.9–6.5	7.5	15	48	0.005
1N825UR	5.9–6.5	7.5	15	19	0.002
1N825AUR	5.9–6.5	7.5	10	19	0.002
1N826UR	6.2–6.9	7.5	15	20	0.002
1N827UR	5.9–6.5	7.5	15	9	0.001
1N827AUR	5.9–6.5	7.5	10	9	0.001
1N828UR	6.2–6.9	7.5	15	10	0.001
1N829UR	5.9–6.5	7.5	15	5	0.0005
1N829AUR	5.9–6.5	7.5	10	5	0.0005

† Double Anode: Electrical Specifications Apply Under Both Bias Polarities.

NOTE 1: Zener impedance is derived by superimposing on I_{ZT} A 60Hz rms a.c. current equal to 10% of I_{ZT} .

NOTE 2: The maximum allowable change observed over the entire temperature range i.e., the diode voltage will not exceed the specified mV at any discrete temperature between the established limits, per JEDEC standard No. 5.

Outline Drawing



LEADED DESIGN DATA

CASE: DO – 213AA, Hermetically sealed glass case.
(MELF, SOD-80, LL34)

LEAD FINISH: Tin / Lead

POLARITY: Cathode end is banded.




MOUNTING POSITION: Any.

MOUNTING SURFACE SELECTION: The Axial Coefficient of Expansion (COE) Of this Device is Approximately +6 PPM/°C. The COE of the Mounting Surface System Should Be Selected To Provide A Suitable Match With This Device.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
D	1.60	1.70	0.063	0.067
F	0.41	0.55	0.016	0.022
G	3.30	3.70	.130	.146
G1	2.54 REF.		.100 REF.	
S	0.03 MIN.		.001 MIN.	



Graphs



Aeroflex / Metelics, Inc.

975 Stewart Drive,
Sunnyvale, CA 94085
Tel: (408) 737-8181
Fax: (408) 733-7645

Sales: 888-641-SEMI (7364)

Hi-Rel Components

9 Hampshire Street,
Lawrence, MA 01840
Tel: (603) 641-3800
Fax: (978) 683-3264

www.aeroflex.com/metelics-hirelcomponents

54 Grenier Field Road,
Londonderry, NH 03053
Tel: (603) 641-3800
Fax: (603)-641-3500

ISO 9001: 2008 certified companies

www.aeroflex.com/metelics metelics-sales@aeroflex.com

Aeroflex / Metelics, Inc. reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties.

Copyright 2010 Aeroflex / Metelics. All rights reserved.



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.