



General ordering data

| | |
|------------------|--|
| Order No. | 1776392001 |
| Part designation | SL-SMT5.08/5/180LF 1.5SN |
| Version | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 5, 180°, Box |
| EAN | 4032248159178 |
| Qty. | 50 pc(s). |

System parameters

| | |
|-----------------------------|--------------------------|
| Fitted to PCB | Reflow solder connection |
| Outgoing elbow | 180° |
| Pitch | 5.08 mm |
| Pitch in inch | 0.2 inch |
| No. of poles | 5 |
| Solder pin length | 1.5 mm |
| Can be coded | Yes |
| No. of solder pins per pole | 1 |
| L1 in mm | 20.32 mm |
| L1 in inch | 0.8 inch |

Material data

| | |
|---------------------------------------|---------------------|
| Insulating material | LCP GF |
| Colour | black |
| colour chart | Similar to RAL 9011 |
| Insulating material group | IIIa |
| Flammability class UL 94 | V-0 |
| Contact base material | CuSn |
| Contact surface | tinned |
| Constant operating temp., min. | -25 °C |
| Constant operating temp., max. | 100 |
| Storage temperature, min. | -25 °C |
| Storage temperature, max. | 55 °C |
| Max. relative humidity during storage | 80 % |

DIN IEC rating data

| | |
|--|-------|
| Rated current, min. No. pins (Tu=20°C) | 19 A |
| Rated current, max. No. pins (Tu=20°C) | 15 A |
| Rated current, min. No. pins (Tu=40°C) | 16 A |
| Rated current, max. No. pins (Tu=40°C) | 13 A |
| Rated voltage for overvoltage class/pollution severity III/3 | 250 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 4 kV |
| Rated voltage for overvoltage class/pollution severity III/2 | 320 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 4 kV |
| Rated voltage for overvoltage class/pollution severity II/2 | 400 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2 | 4 kV |

CSA rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |

Approvals

Approvals institutes



Classifications

| | |
|------------|-------------|
| ETIM 2.0 | NK |
| ETIM 3.0 | EC001284 |
| eClass 4.1 | 27-26-07-01 |
| eClass 5.0 | 27-26-07-01 |
| eClass 5.1 | 27-26-07-04 |

Similar products

| Order No. | Part designation | Version |
|------------|----------------------------------|---|
| 1776362001 | SL-SMT5.08/2/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 2, 180°, Box |
| 1838440000 | SL-SMT5.08/2/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 2, 180°, Box |
| 1776372001 | SL-SMT5.08/3/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 3, 180°, Box |
| 1838450000 | SL-SMT5.08/3/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 3, 180°, Box |
| 1776382001 | SL-SMT5.08/4/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 4, 180°, Box |
| 1838460000 | SL-SMT5.08/4/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 4, 180°, Box |
| 1838470000 | SL-SMT5.08/5/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 5, 180°, Box |
| 1776402001 | SL-SMT5.08/6/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 6, 180°, Box |
| 1838480000 | SL-SMT5.08/6/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 6, 180°, Box |
| 1776412001 | SL-SMT5.08/7/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 7, 180°, Box |
| 1838490000 | SL-SMT5.08/7/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 7, 180°, Box |
| 1776422001 | SL-SMT5.08/8/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 8, 180°, Box |
| 1838500000 | SL-SMT5.08/8/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 8, 180°, Box |
| 1776432001 | SL-SMT5.08/9/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 9, 180°, Box |
| 1838510000 | SL-SMT5.08/9/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 9, 180°, Box |
| 1776442001 | SL-SMT5.08/10/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 10, 180°, Box |
| 1838520000 | SL-SMT5.08/10/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 10, 180°, Box |
| 1776452001 | SL-SMT5.08/11/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 11, 180°, Box |
| 1838530000 | SL-SMT5.08/11/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 11, 180°, Box |
| 1776462001 | SL-SMT5.08/12/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 12, 180°, Box |
| 1838540000 | SL-SMT5.08/12/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 12, 180°, Box |
| 1776472001 | SL-SMT5.08/13/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 13, 180°, Box |
| 1838550000 | SL-SMT5.08/13/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 13, 180°, Box |
| 1776482001 | SL-SMT5.08/14/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 14, 180°, Box |
| 1838560000 | SL-SMT5.08/14/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 14, 180°, Box |

| | | |
|------------|-------------------------------------|---|
| 1776492001 | SL-SMT5.08/15/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 15, 180°, Box |
| 1838570000 | SL-SMT5.08/15/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 15, 180°, Box |
| 1776502001 | SL-SMT5.08/16/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 16, 180°, Box |
| 1838580000 | SL-SMT5.08/16/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 16, 180°, Box |
| 1776512001 | SL-SMT5.08/17/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 17, 180°, Box |
| 1838590000 | SL-SMT5.08/17/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 17, 180°, Box |
| 1776522001 | SL-SMT5.08/18/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 18, 180°, Box |
| 1838600000 | SL-SMT5.08/18/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 18, 180°, Box |
| 1776532001 | SL-SMT5.08/19/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 19, 180°, Box |
| 1838610000 | SL-SMT5.08/19/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 19, 180°, Box |
| 1776542001 | SL-SMT5.08/20/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 20, 180°, Box |
| 1838620000 | SL-SMT5.08/20/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 20, 180°, Box |
| 1776552001 | SL-SMT5.08/21/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 21, 180°, Box |
| 1838630000 | SL-SMT5.08/21/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 21, 180°, Box |
| 1776572001 | SL-SMT5.08/22/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 22, 180°, Box |
| 1838640000 | SL-SMT5.08/22/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 22, 180°, Box |
| 1776582001 | SL-SMT5.08/23/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 23, 180°, Box |
| 1838650000 | SL-SMT5.08/23/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 23, 180°, Box |
| 1776592001 | SL-SMT5.08/24/180LF 1.5SN | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 24, 180°, Box |
| 1838660000 | SL-SMT5.08/24/180LF 3.2SN SW BOX | PCB plug-in connector, Male connectors, Reflow solder connection, Pitch: 5.08 mm, No. of poles: 24, 180°, Box |