

## DATA CENTRE CO-LOCATION CABINET

#### **APPLICATION:**

Hammond's Co-location Rack Cabinet features four (4) different bay configurations. Whether you are leasing the space or want to restrict access to sections of your cabinet, the Hammond CL Series is loaded with innovative features.

#### **FEATURES:**

- One single frame allows multiple bay configurations. Mounting space includes:
  - 1-Bay = 44U, 2-Bay = 21U, 3-Bay = 14U, 4-Bay = 10U
- Standard available configurations available in 36" and 42" depths.
- Vented shelves include rear removable panels for vertical PDU installations.
- Front and Rear Perforated Doors with 65% air flow.
- Doors include 4-pin combination lock with key override.
- Vertical Cable Managers can be installed either top or bottom. Designed to accommodate sliding rail mount kit on servers.
- Cabinet top includes removable top panel and provisions for containment system and cable trough accessories.

#### **SPECIFICATIONS:**

- 14-gauge welded steel frame; 16-gauge doors and side panel.
- Adjustable depth EIA-Compliant Adjustable depth mounting rails.
  - Available as Square Hole or Tapped (10-32) mounting rail.
- Recommended maximum weight load tested for 1,800 lbs.

### **FINISH:**


· Rugged textured black powder paint

#### **ADDITIONAL ACCESSORIES:**


- Third set of rails can easily be added with either 10-32 taps or square holes.
- Security upgrade kit ensures entire cabinet is tamper-proof (see reverse).
- Bay upgrade kit divides a single bay into a 2, 3 or 4 bay cabinet (see reverse).
- Right-hand door hinge kit.



To remove doors; open and lift off.



Vertical Cable
Management can
easily be moved to
top or bottom.



Easily remove cover panels to install a vertical PDU.†



One frame fits all bay configurations. Easily pass cables between cabinets.





# DATA CENTRE CO-LOCATION CABINET

Use this chart to select your desired parts below. You may prefer to visit www.q-assembly.com and build your preferred solution online.				1 Bay (44U)	2 Bay (21U)	3 Bay (14U)	4 Bay (10U)
Step 1	Overall Dimensions 24" (W) x 83.4" (H)	Co-Location Frame is compatible with all bay configurations. In addition, the CL Frame can be used with the hot/cold aisle containment panels.	36" deep	☐ CLF244436BK	☐ CLF244436BK	☐ CLF244436BK	☐ CLF244436BK
			42" deep	☐ CLF244442BK	☐ CLF244442BK	☐ CLF244442BK	□ CLF244442BK
Step 2		19"Tapped 10-32 Rails (Pair)		☐ CLTR44U	☐ CLTR21U	☐ CLTR14U	☐ CLTR10U
19" Mounting Rails		19" Square Hole Rails (Pair)		□ CLSR44U	☐ CLSR21U	☐ CLSR14U	CLSR10U
Step 3		Solid Side Panels (Each)	36" deep	CLSP4436BK (Compatible with all bay configurations)			
Side Panels		Solid Side Panels (Each)	42" deep				
Step 4		Each kit contains the doors, cable _ managers and bay shelves.	36" deep	☐ CL1B36KIT	☐ CL2B36KIT	☐ CL3B36KIT	☐ CL4B36KIT
Internal Kit			42" deep	☐ CL1B42KIT	☐ CL2B42KIT	☐ CL3B42KIT	☐ CL4B42KIT
Step 5		Solid Top Panel		C2T1923SBK1 (Compatible with all bay configurations)			
Top Panel		Vented Top Panel	C2T1923VBK1 (Compatible with all bay configurations)				
Step 6	Solid Bottom Panel 36" deep			CLB2436 (Compatible with all bay configurations)			
Bottom Panel		Solid Bottom Panel	42" deep	CLB2442 (Compatible with all bay configurations)			
Step 7		Baying Kit		GKIT (Compatible with all bay configurations)			
		Grounding Kit	GRDKIT02 (Compatible with all bay configurations)				
		Seismic Bolt-Down Kit		C4K-Z4 (Compatible with all bay configurations)			
		Security Upgrade Kit	CLSECUPG (Compatible with all bay configurations)				
		Cable Trough	CLTROUGH (Compatible with all bay configurations)				
		Right-hand door hinge kit.		☐ CLRHNG (Compatible with all bay configurations) ☐ PDU44U (Compatible with all bay configurations)			
		†PDU Semi-Tooless Mount Bracket		PDU44U (Compa	atible with all bay con	figurations)	

Your QUICK & EASY configuration tool is just a click away!



Build your own assembly at: www.q-assembly.com