# **≣FCi Basics**

## Amphenol ICC

# **USB 3.1 Gen 2 Type C Connector**

Superior performance up to 10Gb/s

### COMPACT, HIGHLY RELIABLE, HIGH SPEED CONNECTOR

USB 3.1 Type C Gen 2 is the future of the USB technology providing multifunction single cable solution for Data, Power, Audio and Video. The slim form factor supports the evolving design trends. The reversible design enables quick and easy connections no matter which way it is inserted. It supports scalable power delivery up to 100W and performance speed up to 10Gb/s.

- Supports SuperSpeed communication 10Gb/s
- Reversible plug and cable orientation
- Slim and sleek design
- Better EMI shielding design



#### **FEATURES**

**BENEFITS** 

<ul> <li>Supports SuperSpeed communication 10Gb/s</li> </ul>	<ul> <li>Minimizes user waiting time</li> <li>Ready for next-generation applications</li> </ul>
<ul> <li>Reversible plug and cable orientation</li> </ul>	<ul> <li>Ensures quick and easy connections whichever way it is inserted</li> </ul>
<ul> <li>Robust and small form factor design</li> </ul>	<ul> <li>Tailored for emerging product designs</li> <li>Suitable for applications in very thin platforms and the I&amp;I market</li> </ul>
<ul> <li>Better EMI (Electromagnetic Interference) shielding design</li> </ul>	<ul> <li>Protects against EMI and ESD (Electromagnetic Discharge)</li> </ul>
<ul> <li>RoHS compliant and lead-free</li> </ul>	Meets environmental, health and safety requirements

### www.amphenol-icc.com

### **TECHNICAL INFORMATION**

#### MATERIAL

- Housing: High Temperature Thermoplastic
- Shell: Stainless Steel
- Terminal: Copper Alloy

#### **MECHANICAL PERFORMANCE**

- Mating Force: 5 to 20N
- Durability: 10,000 mating cycles

#### **ELECTRICAL PERFORMANCE**

- Low Level Contact Resistance:
  - Initial: 40mΩ max.
- $\Delta$  R = +/- 10m $\Omega$  max. after environmental stress
- Insulation Resistance: 100M $\Omega$  min.
- Transfer SuperSpeed: 10Gb/s
- Voltage Rating: 100VAC/DC
- Current Rating:
- 5.0A for VBUS and GND
- 1.25A for Vconn and GND
- 0.25A for all other contacts

#### PACKAGING

- Receptacle: Tape/Reel
- Plug: Tray

### **PART NUMBERS**

#### **SPECIFICATION**

• Amphenol Product Specification: GS-12-1351

#### **ENVIRONMENTAL**

Operating Temperature: -55°C to 85°C

#### **TARGET MARKETS/APPLICATIONS**



#### Infotainment



Flash Drive Laptop Phone Portable Power Bank Portable HDD Tablet Wearable Device



Motherboard Add-on Card Storage Adaptor Storage Enclosure



Factory Automation Equipment Industrial Equipment

Description	Orientation	Mounting Style	Part Numbers
USB 3.1 Type C Gen 2 receptacle	Right angle	Top mount SMT + DIP (Long shell)	10133476-10001LF
USB 3.1 Type C Gen 2 receptacle	Vertical	Top mount dual SMT	10132328-10011LF
USB 3.1 Type C Gen 2 plug	-	-	10133475-10001LF
USB 3.1 Type C Gen 2 receptacle	Right angle	Top mount dual SMT (Short body)	10137737-10001L

### www.amphenol-icc.com

#### Disclaimer