



HRS DRAWING FOR REFERENCE

- NOTES
- 1 THE RECOMMENDED CLAMP TORQUE, REF. NO. 0.15 TO 0.2N·m.
LOCTITE 263, HEKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. 0 FROM LOOSENING.
 - 2 APPLICABLE CABLE: $\phi 14 \pm 0.3$
ASSEMBLE WITH APPLICABLE CONNECTOR (RM24WTP-**(85)).
** SHOWS NUMBER OF CONTACT, AND MALE OR FEMALE OF CONNECTOR.
 - 3
 - 4 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE PLEASE CONFIRM BEFORE THE USE.

3	BRASS	NICKEL PLATING					
2	PHOSPHOR BRONZE	NICKEL PLATING	5	BRASS		NICKEL PLATING	
1	BRASS	NICKEL PLATING	4	CHLOROPRENE RUBBER		(BLACK)	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL		FINISH . REMARKS	

UNITS mm	SCALE	COUNT	DESCRIPTION OF REVISIONS		HY. KISHI	DESIGNED	CHECKED	DATE
			DIS-C	NO.				
	2 : 1	2	18.02.22	18.02.21				

APPROVED : HY. KOBAYASHI	18.02.22	DRAWING NO.	EDC-110117-31-00
CHECKED : HY. KOBAYASHI	18.02.22	PART NO.	RM24WTP-CP(14)(31)
DESIGNED : HY. KISHI	18.02.21	CODE NO.	CL109-1495-6-31
DRAWN : MK. INOUE	18.02.07		

HRS
HIROSE
ELECTRIC
CO., LTD.