2							1						
		ARRAN ECT T CONDI SURFA	TY E'		ON A RESTRICTED BASIS AND IS NOT TO BE US SED OR IMPLIED, IS MADE BY PANDUIT WITH BOND PERFORMANCE. AMONG OTHER THINGS, R WHICH THESE MOUNTS MAY BE APPLIED AND/OR H THEY MAY BE APPLIED ARE BEYOND PANDUIT'S	ed in any v	NAY DETR	RIMENTAL 1	Pane P/		TS OF PANDUIT CORP. WEIGHT 5.20 LB/100 PCS (2368 g/100 PCS		
В	B CABLE ENTRY POINTS (2 PLCS) CABLE CABLE ENTRY POINTS (2 PLCS) CABLE HOLD-DOWNS (3 PLCS) CABLE HOLD-DOWNS (4 PLCS) CABLE HOLD-DOWNS (4 PLCS) (4 PLCS) (4 PLCS) (4 PLCS) (4 PLCS) (4 PLCS) (4 PLCS) (4 P										DG FOR ADDITIONAL ES TO INDICATE GE QUANTITY. MPLETE LIST OF F WITH THIS PART I: BOX COVER BOX BASE X .75" FOAM NG.	- Parts	
4					(2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.3) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2.5) (2						BASE		
A							PART NUMBER CBXJ2**-A TITLE MINI-COM ONE/TWO POSITION SURFACE MOUNT BO CUSTOMER DRAWING ITEM REVISION NAME D35089BI/00 DATASET FILE NAME D35089BI_DC/00B						
							DIMENS	ILESS OTHERN IONAL TOLEF	RANCES	ARE: IN [m			
<pre></pre>	3/18/14	JSP	REFR	MMR	B. REDUCED DRAWING PAGES FORM 2 TO 1. A. REVISED DRAWING TITLE BLOCK.	35089-03	± X. .XX ±	.03[.8]	ANGLES		DRAWING NUMBER:		
+1/Va00101a	10-27-9	5 DW	CEF	CEF	RELEASED TO PRODUCTION	35089–03				HIRD ANGLE ROJECTION	35089-0) 3 size	
	V DATE	BY	СНК	APR	DESCRIPTION	ECN	DW	10-27-95	CEF	NONE	SHT 1 0F 1	A	
					2					1			