

## Han B Side Entry LC M25 Exi\_for DL



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 36 010 1521                                                                        |
| Specification      | Han B Side Entry LC M25 Exi_for DL                                                    |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19360101521">https://b2b.harting.com/19360101521</a> |

### Identification

|                          |                     |
|--------------------------|---------------------|
| Category                 | Hoods/Housings      |
| Series of hoods/housings | Han <sup>®</sup> Ex |
| Type of hood/housing     | Hood                |

### Version

|                      |                                                              |
|----------------------|--------------------------------------------------------------|
| Size                 | 10 B                                                         |
| Version              | Side entry                                                   |
| Cable entry          | 1x M25                                                       |
| Locking type         | Double locking lever                                         |
| Field of application | Connectors for explosion hazardous environments              |
| Details              | ATTENTION! Only to be used with Han <sup>®</sup> Ex inserts! |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Limiting temperature                   | -20 ... +40 °C                                 |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 With cable gland                          |

### Material properties

|                         |                     |
|-------------------------|---------------------|
| Material (hood/housing) | Zinc die-cast       |
| Surface (hood/housing)  | Powder-coated       |
| Colour (hood/housing)   | RAL 5015 (sky blue) |
| RoHS                    | compliant           |
| ELV status              | compliant           |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                |
|--------------------------------------|----------------|
| China RoHS                           | e              |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Not contained  |
| California Proposition 65 substances | Yes            |
| California Proposition 65 substances | Lead<br>Nickel |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 361.5 g                                  |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140181595                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |