



Product: <u>5201FE</u> ☑

Security & Sound, 3 Conductor 16 AWG, BC, Shielded, CMR

Product Description

Security & Commercial Audio Cable, Riser-CMR, 3-16 AWG stranded (19x29) bare copper conductors with polypropylene insulation, Beldfoil® shield, PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications: Intercom/PA Systems, Sound/Audio Systems							
Construction Dataila							
constructi	Construction Details						
Conductor	Conductor						
Element	No. of Elements	s Size	Strandir	ng Material			
Conductor(s)	3	16 AWG	19x29	BC - Bare Copper			
Insulation							
Element	Material	Nom. Thi	ckness I	Nom. Insulation Diame	ter Color Code		
Conductor(s)) PO - Polyolefin 0.008 in (0.20 mm			0.073 in (1.9 mm)	Black, Red, White		
Outer Shield							
Shield Type Material Coverage Drainwire Type							
Tape	Bi-Laminate (Alum+Poly) 100% 24 AWG (7x32) TC						
Outer Jacket							
Material Nom. Thickness Nom. Diameter Ripcord							
PVC - Polyvinyl Chloride 0.017 in (0.43 mm) 0.195 in (4.95 mm) Yes							
Overall Cable Diameter (Nominal): 0.195 in (4.95 mm)							

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	4 Ohm/1000ft	58 pF/ft (190 pF/m)	104.5 pF/ft (342.8 pF/m)	6.25 Amps per conductor @ 25°C

Voltage

UL Voltage Rating
300 V (CMR)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-20°C to +75°C

Bend Radius

Stationary Min.	Installation Min
2.0 in (51 mm)	2.0 in (51 mm)

Max. Pull Tension:	116 lbs (52.6 kg)
Bulk Cable Weight:	34 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor			
Flammability / Reaction to Fire:	UL 1666 Riser, FT4, IEC 60332-1-2			
CPR Compliance:	CPR Euroclass: Eca			
NEC / UL Compliance:	Article 800, CMR			
CEC / C(UL) Compliance:	CMG			
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)			
UK Regulation Compliance:	UKCA Mark			
APAC Compliance:	China RoHS II (GB/T 26572-2011)			
Plenum Number:	6201FE			

History

Update and Revision:

Revision Number: 0.509 Revision Date: 04-28-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
5201FE.00305	Chrome	Reel	305 m	8719605008039	
5201FE 008500	Gray	Reel	500 ft	612825157748	
5201FE 0081000	Gray	Reel	1,000 ft	612825157762	С
5201FE 008U1000	Gray	UnReel	1,000 ft	612825425670	
5201FE 008Z1000	Gray	ReelTuff Box	1,000 ft	612825157786	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.